

TQB Brands Pty Ltd PRICED PRODUCT GUIDE



Established 1984 Trusted by Australia's trade for more than

40 YEARS

VALID THROUGH TO SEPT. 30 2025

ORKSHO



High Clearance Mobile Workshop Table

BMWST

Safe working capacity: 34kg Adjustable working height: 960-1500mm Distance between front casters: 955mm

Caster wheel diameter: 75mm

Table top: 797L x 695W Main tray: 556L x 695W Depth at full width: 485mm Includes top tray liner

FEATURES

Height adjustable to most commercial vehicles.

Smooth rolling castors.

Extra wide legs to suit most commercial vehicles. Multi-functional top table with 2 compartments

and 8 screwdriver holes.

Top EVA mat for skid resistance.

Protective bumper for top tray.

Strong tubular steel construction.

Sturdy main support post.





THE HEIGHT **ADJUSTMENT GIVES YOU PLENTY OF OPTIONS FOR LARGER VEHICLES** AND TRUCKS.

Extra wide legs to suit most commercial vehicles.

Adjustable working height: 960-1500mm

Ball bearing castors ensure you can easily manoeuvre this mobile workshop table around the workshop

Excludes GS

















B

Underhoist Auxiliary Stand 680KG 1198T TRADEQUIP Safe working capacity: 680kg Height: 1370-2045mm Base diameter: 300mm Weight: 16.5kg FEATURES Fast and safe technology for professional mechanics. Heavy gauge steel frame prevents distortion or twisting. Provides partial support for components -NOT designed to support the vehicle. Foot pedal allows easy load movement and hand free operation. height 2045mm Quick action adjustable height mechanism Sold individually recommended only to be used individually. Excludes GST Мах. Inc. GST \$218.90 MADE FOR THE Hands free foot pedal operation



Auxiliary Lifter 500KG

Product information



Scan code to go to our **Top Tips Transmission** Lifter Guide and learn how to extend the life of your TQB Brands equipment



Visit our webpage www.tgbbrands.com.au for instructional & pre-start videos.







Excludes GST

Inc. GST \$746.90

NOT INTENDED FOR

SUPPORTING LOADS AND NOT INTENDED

TRANSMISSION LIFTER

Scissor Lift Workshop Trolley 225KG

6010T TRADEQUIP
the trusted brand in equipment

Safe working capacity: 225kg Working height: 225mm-710mm Table size: 708L x 450Wmm Excludes GST **\$459** Inc. GST \$504.90

MADE FOR THE

FEATURES

Hands free footoperated pedal. Quick release hand lever for easy, controlled release. Heavy duty oilresistant nonslip mat. Powder coated all steel construction. Perfect for moving parts to vehicles.



Scissor Lift Workshop Trolley 500KG

6009T TRADEQUIP

Safe working capacity: 500kg Working height: 265mm-865mm Table size: 820L x 520Wmm



Excludes GST **\$829** Inc. GST \$911.90

FEATURES

Hands free footoperated pedal. Quick release hand lever for easy, controlled release. Heavy duty oilresistant nonslip mat. Powder coated all steel construction. Perfect for moving parts to vehicles.



Scissor Lift Workshop Trolley 300KG

6008T 7 TRADEQUIP

Safe working capacity: 300kg Working height: 350mm-1285mm Table size: 820L x 520Wmm





DOUBLE SCISSOR HIGH

SAFE WORKING 300KG STRADEQUIP G

FEATURES Hands free foot-

operated hydraulic pedal.
Heavy duty oil-resistant nonslip mat.
Powder coated all steel construction.
Perfect for moving parts to vehicles.



Scissor Lift Workshop Trolley 450KG

6003T TRADEQUIP

Safe working capacity: 450kg Working height: 280-875mm Table size: 500 x 810mm Wheel Diameter: 125mm

Wheel Diameter: 125mm Dimensions: 1140L x 515W x 995Hmm



Hands free foot-operated hydraulic pedal. Quick release hand lever. Heavy duty oil-resistant nonslip mat. Powder coated all steel construction. Perfect for moving heavy parts to vehicles.



\$929Inc. GST \$1021.90



FOLDABLE HANDLE

Scissor Lift Workshop Trolley 500KG

6007T TRADEQUIP

Safe working capacity: 500kg Working height: 440-1575mm Table size: 1010L x 520Wmm Wheel diameter: 150mm

Dimensions: 1130L x 520W x 1260Hmm



FEATURES

Double Scissor High Lift.
Foot-operated hydraulic pedal
keeps your hands free.
Quick release hand lever for easy,
controlled hydraulic release.
2 locking heavy duty swivel castors.
All steel construction.

Powder coated for extra protection. Perfect for moving heavy parts to and from the vehicle.

500kg Capacity



CAPACITY 500KG

Excludes GST **\$1699** Inc. GST \$1868.90



Foldable Engine Crane 1,200KG

1001T TO TRADEQUIP

Safe working max. capacity: 1200kg (AS1418.5 approved)

(AS 1416.5 approved)
Adjustable boom: 250kg, 500kg, 750kg & 1200kg
Max. lifting height @ 1200kg: 620mm
Max. lifting height @ 250kg: 1160mm
Jib length fully retracted @ 1200kg: 1040mm
Jib length fully extended @ 250kg: 1580mm

Leg height: 190mm Weight: 85kg

Ideal for automotive & light engineering. Adjustable boom in four positions. Outrigger legs easily fold up for storage. Six swivel castor wheels.

High-grade steel and built to exacting standards for quality and durability.

Short lifting chain & hook with safety latch. Lead-free paint is oil, grease and dirt-resistant for easy cleanup.



Engine Crane Load Leveller 1030 TRADEQUIP

Safe working capacity: 680kg Chain length: 300mm Chain anchor positions: 3 Engine mount positions: 4 Weight: 6kg





Engine Support Bar 1019T TRADEQUIP

Safe working capacity: 500kg Extension: 1020 - 1600mm

Weight: 15kg

FEATURES

Adjusts to fit across most car bonnets Supports engines or transmissions.

Powder coat finish.

Adjustment screw for load leveling. Supplied with short length of chain



Ram to Suit TradeQuip **1001T Engine Crane**

2020

2008 TATRADEQUIP

Safe working capacity: 8,000kg Length: 630-1135mm

Ram pin hole: 16mm dia. 35mm Outside ram Ram diameter: 80mm

Clevis base pin hole: 16mm dia Clevis base: 25mm inside - 45mm outside

Base width: 129mm Weight: 10.5kg

Inc. GST \$189.20

8000 KC capacit

Engine Support Bar

1021T TO TRADEQUIP

Safe working capacity: 500kg Extension: 1020 - 1630mm Weight: 23kg

FEATURES

Cross bar feature for improved

Adjustment screw for leveling.

stability and more flexibility.

Dual hook assemblies for balanced

support of engines & transmissions High gloss enamel finish.



Engine Support Bar

1020T TRADEQUIP

Safe working capacity: 500kg Extension: 1020- 1430mm Weight: 19kg djustable Extension

FEATURES

Dual hook assemblies for balanced support. Adjustable to fit across most car bonnets. Supports engines or transmissions. Rubber cushioned support legs. High gloss enamel finish. Adjustment screw for load leveling.
Supplied with a short length of chain.





Excludes GST Inc. GST \$907.50

Weight: 54kg

360° rotating **WORM GEAR HEAD DRIVE** STURDY REINFORCED NECK

IMPORTANT:

ENGINE DIMENSIONS MUST BE WITHIN LEGS OF ENGINE STAND



Removable legs

360° rotating head Centre height: 895mm 870L x 800W x 900H mm

Weight: 39kg

MADE FOR THE TRADE

Excludes GST

Inc. GST \$303.60

MADE FOR THE TRADE

Engine Stand

TQES450 TRADEQUIP

Safe working capacity: 4cylinder engine only Rated capacity: 450kg 360° rotating head Centre height: 780mm 700L x 750W x 860H mm Weight: 21kg

SPACE SAVING COMPACT DESIGN **EASY SETUP &**

head

IMPORTANT:

ENGINE DIMENSIONS MUST BE WITHIN LEGS OF ENGINE STAND

DISASSEMBLY

Excludes GST Inc. GST \$181.50



IADE FOR THE

Excludes GST

MADE FOR THE

FOLDING LEGS STURDY REINFORCED **NECK AND** STABLE WIDE BASE

Engine Stand

1192T TRADEQUIP

Safe working capacity: 4/5/6/V6/V8 Cylinder less than 6.2ltr Rated capacity: 900kg 360° rotating head Centre height: 800mm 1110L x 530W x 900H mm Weight: 45kg



Car and 4WD Jack Stands



FEATURES

Constructed of high-grade steel & built to exacting standards for quality & durability. Lead-free paint finish is oil, grease and dirtresistant for easy cleanup.

Quick action adjustable height mechanism Double-lock safety pin design for extra safety and security. (1128T & 1148T). Welded steel frame & cast iron support

Adjustable height.
Reinforced shaft for added strength stability. Sold in pairs and only recommended to be used in pairs.



Code	1128T	1148T	1162T
Load limit	2,000kg	4,000kg	8,000kg
Min. Height	285-428mm	395-605mm	468-715mm
Base Area	206x186mm	287x252mm	324x294mm
Excl. GST	\$105	\$181	\$309
Incl. GST	\$115.50	\$199.10	\$339.90



Garage Jack 3,000KG Low Profile

2906T TRADEQUIP

Working load limit: 3,000kg Height: 118 - 488mm Handle length: 1400mm

Front wheels: 90mm dia 40mm width Rear castors: 60mm dia 25mm width

Saddle diameter: 115mm

Dimensions: 670L x 380W x170Hmm Weight: 43kg

FEATURES

Low profile and deep reach. Heavy gauge steel construction.

1400mm long handle for deeper reach. Quick Lift Dual Pump technology .
Internal bypass valve overload protection. Lead-free paint finish to ensure a long-lasting finish and prevent rust. Paint is oil, grease and dirt-resistant Protective foam handle cover prevents



MADE FOR THE

Ratcheting Positioning Jacks

MADE FOR THE

Heavy duty nylon swive

Safe working capacity: 680kg each Max. distance between rollers: 710mm Min. distance between rollers: 340mm Suits tyres up to: 280mm (W) Swivel castors: 100mm

Steel construction with metal rollers

Heavy duty nylon swivel castors.
Easy foot-pedal lifting design.
2 jacks permit full 180° vehicle pivot.
4 jacks place vehicle on a 360° rolling platform.
Lead-free paint finish helps prevent rust and is oil, grease and dirt-resistant for easy cleanup. Quick action adjustable height mechanism. Sold &recommended only to be used in pairs.

Easy foot

pair

TRADEQUIP

Mechanics Creeper 130KG

1023T TRADEQUIP

Safe working capacity: 130kg 1010L x 475W x 115Hmm

MADE FOR THE

Excludes GST

Inc. GST \$101.20

Safe working capacity: 25kg Tray depth: 43mm (inner) Swivel castors: 4 x 50D x16Wmm

435L x 400W x 120Hmm (castor included)

FEATURES

Easy to clean finish that is oil and solvent resistant and won't rust. 4 smooth-rolling swivel castors Impact resistant polymer plastic.
Built-in parts/tool storage compartments



FEATURES

The creeper body is manufactured to "Made for the Trade" quality using a high-impact polymer material that resists impacts, won't rust and is

easy to clean.
Comfortable padded headrest and load capacity of up to 130kg, this low-profile creeper is one of the lightest and most durable available.





488mm

max. lift

height





Wheel Tyre Lifter 1055T TRADEQUIP The trade to be in applyment.

Safe working capacity: 50kg Rollers moving distance: 125mm Roller diameter & length: (D) 76.2 x 240mm Rollers push force: <4kg based on 50kg load Lifting handle force: 1kg based on 50kg load Overall height: 1380mm

Overall base dimensions: 725W x 872D mm Roller working range: 100mm to 1060mm Front castors: 2(D) 75 x 24mm

Rear castor - Locking: 2(D) 75 x 24mm

Weight: 51.25kg

RULY MOBILE.... NO ADDITIONAL AIR LINE OR CHARGING CABLES NEEDED

FEATURES

Braked Swivel Castor Sturdy Frame to safely transport wheel around workshop.
Adjustable Safety Brace.



Braked

MADE FOR THE

For the lifting, lowering, supporting & transporting of tyre & rim assemblies up to 50kgs & 300mm wide.

50kg

Truck Wheel Nut Wrench Torque Multiplier
8033 To TRADEQUIP

1" Drive hand winder operated Trans-speed ratio: 1:56 27mm, 32mm, 33mm, 41mm wheel nut sockets Torque output: 4800Nm

Suitable for Buses



Inc. GST \$185.90

INDIVIDUAL

adjustáble

rollers

The lifters drive screw can be activated by an air or battery-operated ratchet wrench from the top of the unit.

Nut & bolt

storage

trav

79 TRADEQUI

Wheel Dolly Single 250KG B250WH = BORUM

Safe working capacity: 250kg Maximum depth: 305mm Overall height: 1000mm Weight: 14kg

FFATURES

Adjustable arms Adjustable arms. Equipped with rollers for easy positioning. Stop rollers on the rear side. Ergonomic handle with rounded & soft safety grip.

Capacity

This BORUM WHEEL DOLLY is a sturdy & handy transport aid for various types of wheels (trucks, vans, utes and cars). This versatile and easy to operate piece of equipment features adjustable arms. Equipped with two wheels and an ergonomic handle, the units manoeuvrability is not hampered by the size of the wheel.

> Excludes GST Inc. GST \$455.40



INDUSTRIAL

GUALITY



<u>Capacity</u>

Truck Wheel Lifter BTWD750 FAIBORUM

Safe working capacity: 750kg Lift arm spread: 533-635mm Lifting range: 60-275mm Tilt range: -2.5 to 10 degrees 787L x 1092W x 895H mm









online product maintenance

Machined and polished cylinders with die-cut threads provide non-abrasive leak-free, durable performance. Fabricated from hard-cast steel with heat-treated critical stress areas

Unique cross-type forged release valve ensures positive load control.

Overload protection Hydraulic system is protected from internal damage by a by-pass mechanism. High quality glide-action pressure pump. Supplied with 500mm pump handle

Cada	2012	2013	2014	2015	2016
Code	2012	2013	2014	2015	2016
Capacity	10,000kg	15,000kg	20,000kg	12,000kg	20,000kg
Hydraulic Lift	125mm	125mm	145mm	85mm	115mm
Adjustable Height	70mm	70mm	60mm	50mm	75mm
Min. Height	205mm	227mm	245mm	180mm	200mm
Max. Height	400mm	447mm	450mm	315mm	390mm
Base Area	124x124mm	148x136mm	167x156mm	157x134mm	167x156mm
Excl. GST	\$109	\$132	\$169	\$129	\$169
Incl. GST	\$119.90	\$145.20	\$185.90	\$141.90	\$185.90

Air/Hydraulic Bottle Jack 12,000KG

TQBJ12TA TO TRADEQUIP Safe working capacity: 12,000kg Working height: 260-510mm Adjustable screw: 80mm Work pressure: 110-125psi Hydraulic stroke: 170mm Air inlet fitting: 1/4"

FEATURES

Compact powerful Air Turbo motor. Versatile "quick connector provides 'quick & easy air connection. Two piece pump handle. Convenient welded carry handle.

Inc. GST \$240.90

TRADEQUI BOTTLE JAC 2,000kg Capacity

Air/Hydraulic Squat Jack 20,000KG TQBJ20TAS TRADEQUIP

Safe working capacity: 20,000kg Working height: 178-328mm Adjustable screw: 63mm Work pressure: 110-125psi Hydraulic stroke: 87mm

Air inlet fitting: 1/4'

Excludes GST Inc. GST \$339.90





Scan code for online product demonstration 0,000kg Capacity

Air/Hydraulic Bottle Jack 20,000KG 2026T TRADEQUIP

Safe working capacity: 20,000kg Working height: 265-510mm Hydraulic lift: 170mm (265mm to 435mm) Adjustable height: 75mm (max. height 510mm) Base area: 224x134mm Work pressure: 90-120psi Weight: 16kg

FEATURES

Compact powerful Air Turbo motor. Versatile "quick connector provides 'quick & easy air connection.
Two piece pump handle. Convenient welded carry handle

Inc. GST \$317.90



Air Actuated Super Low Profile Jack 20,000KG MADE FOR THE

2051T TG TRADEQUIP

Safe working capacity: 20,000kg Working height: 148-259mm Screw extension height: 45mm Operating air pressure: 100-145psi Hydraulic stroke: 66mm Air inlet fitting: 1/4"

FEATURES

Compact powerful Air Turbo motor Versatile "quick connector provides quick & easy air connection. Chrome plated rams. Convenient welded

carry handle



Inc. GST \$416.90

TRADE







BORUM BOTTLE JACK FEATURES Manufactured of superior-grade steel and built to exacting standards for quality and durability. Lead-free paint finish is oil, grease and dirt-resistant. Built-in by-pass device protects hydraulic system. Compact, powerful Air Turbo Motor.
High quality large diameter hydraulic steel cylinder.
Precision machined, chrome plated and polished piston-ram.
Versatile "quick connector" for easy removal of air hose.



Air/Hydraulic Bottle Jack 20,000KG

BTSJ20TB /= BORUM Safe working capacity: 20,000kg Working height: 262 - 504mm Hydraulic lift: 163mm

Op. air pressure: 110-125psi Air inlet fitting: 1/4"

Weight: 16kg **Excludes GST**

Excludes GST

Inc. GST \$427.90

20,000kg **Capacity** INDUSTRIAL QUALITY



Air/Hydraulic Bottle Jack 20,000KG

BWBBJ20T = BORUM Safe working capacity: 20,000kg Working height: 263 - 503mm Hydraulic lift: 160mm Adjustable height: 80mm Base area: 200x152mm Op. air pressure: 90-120psi



Air/Hydraulic Bottle Jack 30,000KG

BWBBJ30T /= BORUM Safe working capacity: 30,000kg Working height: 275 - 532mm Hydraulic lift: 162mm Adjustable height: 95mm Base area: 229x180mm Op. air pressure: 90-120psi

INDUSTRIAL QUALITY **Excludes GST**

Inc. GST \$548.90



Air/Hydraulic Bottle Jack 35,000KG

BBJ35TA BORUM Safe working capacity: 35,000kg Working height: 264 - 414mm Hydraulic lift: 150mm Operating air pressure: 110-125psi Air inlet fitting: 1/4 Weight: 29kg





FEATURES OF TQ Pro BOTTLE JACKS
Using CNC technology, TQ Pro products
are constructed using superior-grade steel
and built to premium TQ Pro standards

for professional quality and durability.

Trusted by serious prof
Premium quality large diameter hydraulic steel cylinders are machi
then treated and polished to minimise wear and extend service life

Incorporating the latest technology in aggressive wiping lips and OD exclusion, the high capability premium quality seal systems efficiently protect internal hydraulics keeping it free from dirt, mud,

premium quality sear systems contactly provided the water, and other contaminants.

A lead-free paint finish is applied after a thorough chemical wash to ensure a long-lasting premium finish with a final coat that is oil, grease and dirt-resistant for easy cleanup.

Air/Hydraulic Bottle Jack 20,000KG

PROBJ20TA Safe working capacity: 20,000kg Working height: 261.5-525mm Hydraulic lift: 156mm Adjustable lift: 95mm Operating air pressure: 110-125psi Air inlet fitting: 1/4" Base: 230 x 150 x 30mm

Weight: 19kg

Professional Outstanding

Excludes GST Inc. GST \$493.90



Excludes GST

Inc. GST \$493.90

Air Actuated Bottle Jack Squat 20,000KG

PROBJ20TAS

Safe working capacity: 20,000kg Working height: 185-330mm Hydraulic lift: 80mm Operating air pressure: 110-125psi

Adjustable height: 61mm Air inlet fitting: 1/4"
Base: 230 x 150 x 30mm Weight: 16kg



Professional Reputable Outstanding



Air/Hydraulic Bottle Jack 30,000KG

PROBJ30TA Safe working capacity: 30,000kg Working height: 279.5-533mm Hydraulic lift: 155mm Op. air pressure: 110-125psi Air inlet fitting: 1/4" Base: 250 x 180 x 40mm Weight: 29kg

PRO **Professional**

Reputable Outstanding

Excludes GST Inc. GST \$647.90



ick Jack Stands 🖊 🗀 B D R U M

SOLD INDIVIDUALLY

		7-
Code	15TJSSHORT	15TJS
Load limit	15,000kg	15,000kg
Height	446 - 631mm	645-1077mm
Base Area	300x300mm	460x460mm
Excl. GST	\$439	\$529
Incl. GST	\$482.90	\$581.90
Code	25TJSSHORT	25TJS
Load limit	25,000kg	25,000kg
Height	415 - 539mm	680-968mm
Base Area	300x300mm	460x460mm
Excl. GST	\$539	\$599
Incl. GST	\$592.90	\$658.90



FEATURES

Manufactured from high-grade steel and built to exacting standards for

quality and durability. Lead-free paint finish is oil, grease and dirt-resistant for easy cleanup. High strength locking pin. Controlled pin holes for easy height adjustments.

Turned post slide for easy quick

adjustments.

Heavy-gauge steel gusseted uprights prevent distortion or twisting. Rugged base provides plenty of stability.

Conveniently located carry handle. Sold individually. (not in pairs)

INDUSTRIAL



Auxiliary Stand 7,000KG BAUXS7T /= BORUM

Safe working capacity: 7,000kg Working height: 1295-1905mm Adjustable pin heights: 8 (75mm increments) Base: 300x300x300mm

Weight: 65kg **FEATURES**

Heavy duty design and support bracing system to sustain heavy vehicle loads.

Manufactured from high-grade steel and built to exacting standards for quality and durability.
Fitted with spring loaded castor

wheels to ensure easy movement around the workshop

Fitted with spring loaded support

beam. Lead-free paint finish is applied after a thorough chemical wash to ensure a long-lasting finish and to help prevent rust. Paint is oil, grease and dirt-resistant for easy cleanup. High strength locking pin. Controlled pin holes for easy height adjustments.
Turned post slide for easy quick adjustments

3 saddle options: 90mm, 120mm, up to 150mmØ



Spring loaded castor wheels





Safe working capacity: 10,000kg Working height: 720-1190mm Adjustable pin heights: 10 Saddle dimensions: 150x80mm Base: 406 x 556mm Weight: 23.5kg

FEATURES

Stable 4 legged stability. Lead-free paint is oil, grease and dirt-resistant for easy cleanup. High strength locking pin & controlled pin holes for easy height adjustments. Turned post slide for easy adjustment.

*10TSS/10TSSHORT SOLD INDIVIDUALLY

Support Stand SHORT 10,000KG PA BORUM 10TSSHORT

Safe working capacity: 10,000kg Working height: 480-780mm Adjustable pin heights: 6 Saddle dimensions: 150x80mm Base: 310 x 310mm Weight: 18kg

Inc. GST \$405.90

10 Metric Sizes:

Weight: 14kg

10 Piece Metric

B10PJSM = BORUM

34mm, 36mm, 38mm, 41mm, 42mm, 44mm, 45mm, 46mm, 48mm & 50mm

Wallet rolled out: 830 x 690 x 30mm

Wallet rolled up: 150 x 690 x 130mm

Inc. GST \$456.50

INDUSTRIAL

Capacity

Excludes GST

Jumbo Spanner Set Jumbo Spanner Set 10 Piece Imperial

B10PJSI Z= BORUM

10 Imperial Sizes: 1 5/16", 1 3/8", 1 7/16", 1 1/2", 1 5/8", 1 11/16", 1 3/4", 1 13/16", 1 7/8" 2" Wallet rolled out: 830 x 690 x 30mm Wallet rolled up: 150 x 690 x 130mm Weight: 14kg

Excludes GS1 GST \$284.90



Inc. GST \$284.90









Inc. GST \$1703.90





Air Actuated Truck Jack 22,000KG

B2003T Z= BORUM

Safe working capacity: 22,000kg Lift range: 210-525mm Hydraulic lift: 120mm Adjustable height: 105mm Handle length: 1075mm Air supply: 100-120psi Wheel diameter: 175mm

Adaptors: 20, 50, 100mm Chassis: 500L x 215H x 320Wmm

FFATURES

Solid heavy duty construction.
Advanced technology sealing rings.
Fast motion super duty air pump.
Temperature-resistant hydraulic oil. Treated and polished piston and ram. Built-in bypass hydraulic safety overload system. Compact design easily fits dual tandem

Convenient & efficient height adaptors. 3-position pumping handle. High quality lead-free paint is oil, grease and dirt-resistant finish for easy cleanup.









Air Actuated Truck Jack 22,000KG

2004T TRADEQUIP

Safe working capacity: 22,000kg Lift range: 225-552mm Hydraulic lift: 124mm Adjustable height: 103mm Chassis: 560L x 230H x 320Wmm Adaptors: 21, 60, 100mm Handle length: 1160mm Wheel diameter: 200mm







FEATURES

Trade quality rugged steel construction. Wear-resistant quality sealing O-rings. Strong hydraulic pump.
Temperature-resistant hydraulic oil.
Treated and polished piston and Quick lift ram. Built-in bypass hydraulic safety overload system. Compact design easily fits dual tandem axles. Convenient & efficient height adaptors. 3-position pumping handle High quality lead-free paint is oil, grease and dirt-resistant finish for easy cleanup.

Air Actuated Truck Jack 20,000KG PROTRJA20T

Safe working capacity: 20,000kg Working height: 215-541mm Hydraulic Lift: 141mm Adjustable screw: 85mm Adaptors: 20, 50, 100mm Handle length: 1335mm Operating air pressure: 145-175psi Chassis: 520L x 215H x 258Wmm





FEATURES

Double sealing using XTP industry sealing Telescopic air actuation lift (air-hydraulic pump) Long T-handle lets you easily position your jack under vehicle.

Self-returning lowering and lifting switch.
Internal and external cylinders hard chromed
High manoeuvrability & deep reach. 3 extension adaptors/saddle plates







Professional Reputable Outstanding



Air Jack Support Stand 10,000KG BSJ10T - BORUM

Safe working capacity: 10,000kg Height: Min. 444mm - Max. 1298mm Hydraulic lift: 292mm Base diameter: 339mm

Rated air pressure capacity: 200psi Weight: 91kg

Excludes GS1 Inc. GST \$1483.90



FFATURES

The BORUM Industrial AIR JACK/SUPPORT STAND 10,000KG is a reinforced pin style jack and stand with industrial quality design and support bracing system to sustain heavy loads up to 10,000kg. Adjusts to match the job with a 444mm minimum height, 292mm of hydraulic lift and up to 1298mm maximum height using the extension tube!!

Featuring Heavy-Duty Industrial design, this tough air jack/support stand is ideal for truck, bus, farm, earthmoving equipment and fleet vehicle maintenance workshop use.





grips are bolted and glued to the 6mm steel floor plates and they will not skid ahead of the wheels.

Replaces need for a pit or hoist, and at a fraction of the cost and floor space

Air Actuated Truck Jack 35,000KG

BTJ35TA /= BORUM

Safe working capacity: 35,000kg Lift range: 255-633mm Hydraulic lift: 155mm Adjustable height: 123mm

Adaptors: 21, 61, 100mm Handle length: 1110mm

Operating air pressure: 110-125psi Chassis: 555L x 255H x 295Wmm

FEATURES

Pro quality rugged steel construction. Wear-resistant quality sealing O-rings. Strong hydraulic pump & 3-position handle. Temperature-resistant hydraulic oil. Treated and polished piston and ram Related and pointed spisor and rain.

Built-in bypass hydraulic safety overload.

Compact design and Quick Lift ram.

Convenient & efficient height adaptors. High quality lead-free paint.



Includes Height **Adaptors**

LIFTS

35.000KG

Includes Height **Adaptors** Air Actuated Jack 2 Stage 15,000/30,000KG

BTJ1530TA /= BORUM

1st stage: 30,000kg safe working capacity 2nd stage: 15,000kg safe working capacity First stage hydraulic lift: 73mm Second stage hydraulic lift: 66mm Operating air pressure: 145-175psi

Height: 150-409mm Adaptors: 45 and 75mm Handle length: 1300mm Chassis: 480 x 290 x 150mm

> Includes Height **Adaptors**

FEATURES

Double sealing function using XTP industry sealing.
Telescopic air actuation lift (airhydraulic pump). Long T-handle lets you easily position your jack under vehicle. Self-returning lower & lift switch .
Internal and external cylinders hard

chromed. High manoeuvrability & deep reach under vehicles.

2 extension adaptors/saddle plates Large rubber wheels











Inc. GST \$2726.90



Air Actuated Truck Jack 50,000KG

BTJ50TA BORUM

Safe working capacity: 50,000kg Lift range: 287-650mm Hydraulic lift: 153mm Adjustable screw: 110mm Adaptors: 20, 60, 100mm Handle length: 1230mm Operating air pressure: 110-125psi Chassis: 525L x 288H x 325Wmm



FEATURES

Pro quality rugged steel construction. Wear-resistant quality sealing O-rings. Strong hydraulic pump & 3-position handle. Temperature-resistant hydraulic oil. Treated and polished piston and ram.
Built-in bypass hydraulic safety overload.
Compact design and Quick Lift ram. Convenient & efficient height adaptors High quality lead-free paint

Air Actuated Truck Jack 30,000KG

BTJ30TA Z= BORUM Safe working capacity: 30,000kg Lift range: 360-772mm Hydraulic lift: 267mm Adaptors: 45 & 100mm

Handle length: 1370mm Operating air pressure: 145-175psi Chassis: 840L x 360H x 282Wmm



Inc. GST \$1846.90

50.000KG

30.000KG

Includes Height

FEATURES

XTP industry double sealing function using Telescopic air actuation lift.
Self-returning lowering and lifting switch. Internal & external cylinders hard chromed Long T-handle for high manoeuvrability & deep reach under vehicles Designed for extremely high axles



Air Actuated Truck Jack 60,000KG

BTJ60TA /= BORUM

Safe working capacity: 60,000kg Lift range: 420-1031mm Hydraulic lift: 311mm Adaptors: 100 & 200mm Handle length: 1290mm Operating air pressure: 145-175psi Chassis: 910L x 420H x 300Wmm





FEATURES

Double sealing function using XTP industry sealing.

Telescopic air actuation lift. Self-returning lowering and lifting switch.
Internal & external cylinders hard chromed Long T-handle for high manoeuvrability & deep reach under vehicles.

Designed for extremely high axles



Includes Height **Adaptors**









Air Actuated 2 Stage Truck Jack 10,000/25,000KG

BTJ1025TA = BORUM

Stage 1: 25,000kg safe working capacity Stage 2: 10,000kg safe working capacity

Lift range: 185-497mm

Hydraulic lift: Stage1: 97mm, Stage2: 95mm

Adaptors: 45, 75mm Handle length: 1380mm

Operating air pressure: 145-175psi Chassis: 770L x 282H x 185Wmm



FEATURES

Includes Height **Adaptors**

Double sealing function - XTP industry sealing. Telescopic air actuation lift. Self-returning lowering and lifting switch.
Internal & external cylinders hard chromed Long T-handle for high manoeuvrability & deep reach under vehicles

Air Actuated 2 Stage Truck Jack 25,000/50,000KG

BTJ2550TA = BORUM

Stage 1: 50,000kg safe working capacity Stage 2: 25,000kg safe working capacity Lift range: 215-564mm

Hydraulic lift: Stage1: 115mm, Stage2: 114mm

Adaptors: 45, 75mm Handle length: 1380mm

Operating air pressure: 145-175psi Chassis: 805L x 282H x 215Wmm



LIFTS

Includes Height Adaptors

LIFTS

25.000KG

50,000KG

Double sealing function - XTP industry sealing. Telescopic air actuation lift. Self-returning lowering and lifting switch. Internal & external cylinders hard chromed Long T-handle for high manoeuvrability & deep



Air Actuated 3 Stage Truck Jack 10,000/25,000/50,000KG

BTJ102550TA - BORUM

Safe working capacity: Stage 1: 50,000kg Stage2: 25,000kg, Stage3: 10,000kg Lift range: 160-472mm Hydraulic lift: Stage1: 62mm Stage2: 61mm, Stage3: 69mm Adaptors: 45, 75mm Handle length: 1380mm

Operating air pressure: 145-175psi Chassis: 825L x 282H x 160Wmm



50.000KG



FEATURES

Double sealing function using XTF industry sealing.
Telescopic air actuation lift

Self-returning lowering and lifting switch.
Internal & external cylinders hard chromed
Long T-handle for high manoeuvrability &



Air Actuated 3 Stage Truck Jack 20,000/40,000/60,000KG

BTJ204060TA = BORUM



First stage: 60,000kg safe working capacity Second stage: 40,000kg safe working capacity Third stage: 20,000kg safe working capacity First stage hydraulic lift: 57mm

Second stage hydraulic lift: 59mm Third stage hydraulic lift: 61mm

Height: 150-447mm Adaptors: 45 and 75mm

Operating air pressure: 145-175psi Handle length: 1380mm Chassis: 875 x 295 x 150mm

> **Includes** Height **Adaptors**



Inc. GST \$4508.90



FEATURES

Double sealing function using XTP industry sealing Telescopic air actuation lift (air-hydraulic pump). Long T-handle lets you easily position your jack under vehicle

Self-returning lowering and lifting switch Internal and external cylinders hard chromed .
High manoeuvrability & deep reach under vehicles. 2 extension adaptors / saddle plates. Large rubber wheels



Air Actuated 2 Stage Truck Jack 50,000/80,000KG

BTJ5080TA /= B O R U M

First stage: 80,000kg safe working capacity Second stage: 50,000kg safe working capacity First stage hydraulic lift: 111mm

Second stage hydraulic lift: 102mm Height: 230-563mm

Adaptors: 45 and 75mm Operating air pressure: 145-175psi Handle length: 1300mm Chassis: 930 x 340 x 230mm



Inc. GST \$5058.90






Includes Height **Adaptors**

FEATURES

Double sealing function using XTP industry sealing. Telescopic air actuation lift (air-hydraulic pump). Long T-handle lets you easily position your jack under vehicle

Self-returning lowering and lifting switch. Internal and external cylinders hard chromed .
High manoeuvrability & deep reach under vehicles 2 extension adaptors / saddle plates Large rubber wheels

















Visit our webpage www.tqbbrands.com.au for more specifications and images



Excludes GS1

*FREIGHT **RATES WILL** APPLY



YouTube

Scan code for online product demonstration

*NOTE: ADDITIONAL TOOLING MAY BE REQUIRED FOR SOME APPLICATIONS











0



TRADEQUIP

MORE THAN JUST A PRESS!

Workshop Mate Workstation featuring a 30,000KG Shop Press & Spring Compressor

MADE FOR THE



Safe working capacity: 30,000kg Working range: 224mm-819mm Piston ram stroke main ram: 140mm (Standard load cap fitted)

Bed height settings: 85mm increments-8 settings

Bed width: 466mm Bed gap: 200mm

Spring compressor: Piston ram stroke: 295mm

Operating air pressure: 90-125psi

Overall dimensions: 1820H x 1170W x 820Dmm

Weight: 400kg



FEATURES

AIR/HYDRAULIC OPERATED 30,000KG PRESS SPRING COMPRESSOR.

FILTER CRUSHING ACCESSORY DOZENS OF UNIQUE TOOLING OPTIONS **ON-BOARD TOOLING STORAGE STAND** WINCH OPERATION TO LOWER AND RAISE BENCH

BENEFITS

Press almost any bearing or bush with PRECISION and ACCURACY in minutes, saving valuable workshop time. Smooth AIR/HYDRAULIC foot pedal operation for handsfree accuracy & control.

Hands free Spring Compression.

Even the most difficult pressing tasks become SAFE &

Complete with **COMPREHENSIVE HIGH QUALITY** Interlocking Tool, Die and Spacer Kit to ensure SAFE WORK PRACTICES.

Complete on machine storage - minimises time spent searching for the required tools & spacers for each job! Tasks like **SUSPENSION BUSHES** once seen as too hard become a breeze.

A comprehensive variety of spring adaptors, suitable to almost any type or model of spring SAFE & EASY to compress in minutes.

Decrease labour time & increase productivity and

INCREASE WORKPLACE SAFETY.

Undertake jobs that are currently too difficult.

Workshop Mate 18 Pce Sleeve Kit



18 Piece Sleeve Set includes. 28x20x80mm: 33x25x80mm: 38x30x80mm; 43x35x80mm; 48x40x80mm; 53x45x80mm; 58x50x80mm; 63x55x80mm; 68x60x80mm; 73x65x80mm; 78x70x80mm; 83x75x80mm; 88x80x80mm; 93x85x80mm; 98x90x80mm; 103x95x80mm; 108x100x80mm; 113x105x80mm

FEATURES

18 sleeves constructed from heat-treated forged carbon steel. Sturdy metal carry case. Designed and engineered to work as an added accessory to all current Workshop Mate Workstations.



Great Workshop Mate Accessory



Workshop Press 20,000KG

1061T TRADEQUIP

Safe working capacity: 20,000kg Working range: 60-773mm Overall height: 1503mm Overall width: 705mm BARRIER Overall depth: 660mm AVAILABLE Bed width: 504mm SEPARATELY

Bed gap: 103mm Bed inside: 285 x 103mm Press head diameter: 40mm Press head length: 68mm Jacking handle: 694mm Piston ram stroke: 160mm





FFATURES

Weight: 82kg

High-grade Channel Steel Hydraulics are powered with a high

quality oil.
Integrated overload protection valve keeps from overloading the system. Lead-free paint finish is oil, grease and dirt-resistant for easy cleanup and to help prevent rust.



Workshop Press 30,000KĠ

1062T TRADEQUIP

Safe working capacity: 30,000kg Working range: 45-705mm Overall height: 1605mm Overall width: 745mm BARRIER Overall depth: 660mm AVAILABLE Bed width: 480mm SEPARATELY Bed gap: 124mm Bed inside: 254 x 124mm Press head diameter: 50mm Press head length: 68mm Jacking handle: 694mm



FFATURES

High-grade Channel Steel Hydraulics are powered with a high

Integrated overload protection valve keeps from overloading the system. Lead-free paint finish is oil, grease and dirt-resistant for easy cleanup and to help prevent rust



Hydraulic Workshop Press 20,000KG

1063T TRADEQUIP

Safe working capacity: 20,000kg Working range: 43-882mm Overall height: 1795mm Overall width: 780mm Overall depth: 690mm Bed width: 505mm Bed gap: 105mm Bed Inside: 358 x 105mm Press head cap diam: 45mm Press head cap length: 17mm Ram lateral adjustment: 180mm Piston ram stroke: 185mm Weight: 90kg

FEATURES

High-grade Channel Steel. 100mm pressure gauge. High quality large diameter hydraulic steel cylinder unit.

Hydraulics are powered with a high quality oil.

Integrated overload protection valve keeps from overloading the system. Lead-free paint finish is oil, grease and dirt-resistant for easy cleanup and to help prevent rust.

Lateral Ram Adjustment





Hydraulic Workshop Press 30,000KG

1064T TRADEQUIP

Safe working capacity: 30,000kg Working range: 50-1030mm Overall height: 1950mm Overall width: 830mm Overall depth: 660mm Bed width: 455mm Bed gap: 154mm Bed inside: 230 x 154mm Press head diameter: 56mm Load cap length: 17mm

Jacking Handle: 639mm Ram lateral adjustment: 70mm Piston ram stroke: 170mm Weight: 138kg

FEATURES

High-grade Channel Steel 100mm pressure gauge.
High quality large diameter hydraulic steel cylinder unit. Hydraulics are powered with a high

quality oil.
Integrated overload protection valve keeps from overloading the system. Lead-free paint finish is oil, grease and dirt-resistant for easy cleanup and to help prevent rust.

Lateral Ram Adjustment





SAFETY








Hydraulic Workshop Press 45,000KG WIDE

2036T TRADEQUIP



Bed inside: 195mm Bed width: 826mm Piston ram stroke: 190mm Ram diameter: 90mm 1707H x 1420W x 826Dmm Bed height settings: 6



FEATURES

Weight: 296kg

High-grade steel frame. 100mm pressure gauge. Bed winch for easy raise and lower adjustment. Lead-free paint finish is oil. grease and dirt-resistant. Hand winch for fast adjustment

Air/Hydraulic Workshop Press 45,000KG WIDE

2038T TRADEQUIP

Safe working capacity: 45,000kg Working range: 159-859mm Bed outside: 359mm Bed inside: 195mm Bed width: 826mm Piston ram stroke: 190mm Ram diameter: 90mm Op. air pressure: 110-125 psi 1707H x 1420W x 800Dmm Bed height settings: 6 Weight: 301kg

AIR OPERATED

FEATURES

High-grade steel frame. 2 speed pump. 100mm pressure gauge.
Bed winch for easy raise
and lower adjustment.
Paint is oil, grease and dirtrain is oil, grease and diff-resistant for easy cleanup. High quality large diameter hydraulic steel cylinder unit. Piston-ram is treated, polished. Includes hand winch Integrated overload protection valve prevents

overloading.
Extra-long handle included for easy pumping force.
Double spring ram return for fast ram retraction











HEIGHT SETTINGS





Hydraulic Workshop Press 50,000KG

TO TRADEQUIP

2048T TATRADEQUIP

Safe working capacity: 50,000kg Working range: 137-837mm Bed outside: 356mm Bed inside: 210mm Bed width: 713mm Bed internal: 390 x 200mm Piston ram stroke: 190mm

MADE FOR THE

Ram diameter: 95mm Op. air pressure: 110-125 psi 1700H x 1290W x 745Dmm Bed height settings: 6 Weight: 271kg

SALETA

BARRIER MAULABLE

SEPARATELY



FEATURES

Heavy-duty high-grade steel frame. Hand operated air trigger ram travel control. 100mm pressure gauge Polished pneumatic aluminium air motor Bed winch for easy raise and lower adjustment. Lead-free paint finish helps prevent rust& is oil grease and dirt-resistant. High quality large diameter hydraulic unit. Hand winch for fast height adjustments



Workshop Press Adaptor Kit

BPAK - BORUM

Includes 8 different sized pins (mandrels) ranging from 2,000kg to 20,000kg capacity, a pin holder, a storage shelf along with a mounting kit, and a pin plate with the weight capacity shown for each pin. This very handy set of eight steel mandrels,

adaptor and press plate expands the uses of your workshop press for a wider range of applications involving different sized work pieces.





Mandrel Length x Diameter

50mm x 10mm 60mm x 12mm

60mm x 16mm 85mm x 18mm

85mm x 20mm 85mm x 22mm

15mm x 25mm 110mm x 30mm





***UNLESS STATED OTHERWISE, ALL TQB BRANDS PRODUCTS, EXCLUDING CONSUMABLES, COME WITH A 12 MONTH COMMERCIAL USE WARRANTY AGAINST MANUFACTURING DEFECTS. THE BONUS 12 MONTH WARRANTY OFFERED EXCLUSIVELY IN THIS PROMOTIONAL PERIOD APPLIES ONLY TO THE HYDRAULIC RAM AND HYDRAULIC PUMP FOR BONUS" MARKED PRODUCTS. THE ADDITIONAL 12 MONTHS DOES NOT INCLUDE INSTALLATION/REMOVAL LABOUR OR FREIGHT FOR THE COMPONENT

Air/Hydraulic Workshop Press 30,000KG 6 HEIGHT

PROSHPR30TA

Safe working capacity: 30,000kg Working range: 25-850mm Screw adjustment: 75mm Bed outside: 164mm Bed inside: 148mm Bed width: 600mm Ram diameter: 58mm Bed height settings: 6

BARRIER SEPARATELY

SETTINGS

1800H x 770W x 505Dmm Weight: 163kg

LATEST APPLIED TECHNOLOGIES

30,000kg Capacity

LATEST APPLIED

- ✓ Mandrel Kit Included
- ✓ Long Pump Handle
- **Premium Bed Blocks**
- Winch Adjustable Bed
- Premium Hydraulic System
- ✓ Premium Paint Finish
- **Precision Lateral Ram Adjustment**
- **Premium Grade Steel Construction**
- Designed for maximum strength, reliability and durability

Foot Pedal Air/Hydraulic Operation



OPRO

Excludes GST

PRO



TQPro Presses online product demonstration

Air/Hydraulic **Workshop Press** 50,000KĠ

PROSHPR50TA Safe working capacity: 50,000kg

Working range: 80-780mm Screw adjustment: 75mm Bed inside: 200mm Bed outside: 220mm Bed width: 750mm Ram diameter: 68mm

Bed height settings: 6 1900H x 930W x 535Dmm Weight: 243kg











Inc. GST \$5388.90

Hydraulic Workshop Press 20,000KG BHSP20T /= BORUM

Safe working capacity: 20,000kg Working range: 38-918mm

Bed outside: 172mm Bed inside: 152mm Bed width: 510mm Piston ram stroke: 185mm Bed height settings: 8 Ram diameter: 72mm 1626H x 755W x 560Dmm



FEATURES

Weight: 115kg

Heavy-duty high-grade steel H-frame. Integrated overload protection valve Foot & Hand operated pump. 100mm pressure gauge STEEL SAFETY MESH BARRIER Lead free paint finish is oil, grease and dirt-resistant for easy cleanup.
Piston-ram is fitted with backup ring, preventing bypass oil drift. High quality hydraulic oil offers better corrosion resistance and flexibility. Pair of bed plates included.





Hydraulic Workshop Press 30,000KG BHSP30T /= B O R U M

Safe working capacity: 30,000kg Working range: 151-1031mm Bed outside: 184mm Bed inside: 164mm Bed width: 535mm Piston ram stroke: 150mm Bed height settings: 8 Ram diameter: 80mm 1830H x 1000W x 700Dmm Weight: 167kg



FEATURES

Heavy-duty high-grade steel H-frame. Integrated overload protection valve. Foot & Hand operated

pump. 100mm pressure gauge STEEL SAFETY MESH BARRIER

Lead free paint finish is oil, grease and dirt-resistant for easy cleanup.
Piston-ram is fitted with

backup ring, preventing bypass oil drift. High quality hydraulic oil offers better corrosion

resistance and flexibility. Pair of bed plates included.

Inc. GST \$3078.90











Air/Hydraulic Workshop Press 75,000KG BSP75TA Z= BORUM

Safe working capacity: 75,000kg Working range: 170-884mm Overall height: 1925mm Overall width: 1340mm Overall depth: 800mm Bed width: 800mm Bed surface depth: 279mm

Piston ram stroke: 250mm Ram diameter: 125mm Width between side posts: 217mm Bed height settings: 8 Operating air pressure: 110-125psi

Air inlet: 1/4"NPT Weight: 451kg

Power to safely remove & install bearings, gears, U-joints, bushings, ball joints and pulleys with precision and versatility!



Air/Hydraulic Workshop Press 100,000KG

Safe working capacity: 100,000kg Working range: 113-813mm Overall height: 1848mm Overall width: 1250mm Overall depth: 990mm Bed width: 787mm Bed surface depth: 342mm

Piston ram stroke: 300mm Ram diameter: 140mm Width between side posts: 268mm Bed height settings: 6 Operating air pressure: 110-125psi

Air inlet: 1/4"NPT Weight: 652kg

Ideal for straightening, stamping, bending and pressing any component that is difficult to handle.

6 HEIGHT

OUALITY



- Heavy-duty H-frame constructed of high-grade steel and built to exacting standards for quality and durability.
 Foot operated air trigger ram travel control.
 100mm pressure gauge.
 Extra tall working range for versatility.
 Pair of bed plates included
- Table winch system lowers or raises the bed. Integrated overload protection valve keeps from overloading the system.
- High quality large diameter hydraulic steel cylinder unit results in lower oil pressure needed to raise the load, helping to reduce wear and extend service life.
- Piston-ram is treated and polished and fitted with backup ring, preventing load from falling slowly or bypassing oil drift.

 Hydraulics are powered with a high quality oil, which offers better corrosion resistance & high/low temperature flexibility, allowing the unit to operate at temperatures.
- Léad-free paint finish is applied after a thorough chemical wash to ensure a long-lasting finish to help prevent rust & is oil, grease, & dirt-resistant for easy clean up.

***UNLESS STATED OTHERWISE, ALL TOB BRANDS PRODUCTS, EXCLUDING CONSUMABLES, COME WITH A 12 MONTH COMMERCIAL USE WARRANTY AGAINST MANUFACTURING DEFECTS. THE BONUS 12 MONTH WARRANTY OFFERED EXCLUSIVELY IN THIS PROMOTIONAL PERIOD APPLIES ONLY TO THE HYDRAULIC RAM AND HYDRAULIC PUMP FOR "BONUS" MARKED PRODUCTS. THE ADDITIONAL 12 MONTHS DOES NOT INCLUDE INSTALLATION/REMOVAL LABOUR OR FREIGHT FOR THE COMPONENT

Polycarbonate TQB Shop Press Safety Barrier

TRADEQUIP

SUIT TQB BRANDS PRESSES ONLY



Multiple Height Settings

SGUARD-1

PRESS GUARD POLY CARBONATE SUIT 1061/1062/1063T



SGUARD-3

PRESS GUARD POLY CARBONATE SUIT BSP75TA



SGUARD-2 PRESS GUARD POLY CARBONATE

SUIT 1064T



SGUARD-4

PRESS GUARD POLY CARBONATE SUIT 2048T/2038T/ 2036T/BSP100TA

Great Workshop Press Safety Accessory *DOES NOT INCLUDE PRESS AND ACCESSORIES SHOWN **FWD Wheel Bearing**

* * * * AVAILABLE IN FOUR DIFFERENT SIZES * * *

Master Press & Pull Set 28 Piece

9028T TRADEQUIP

4 x Step plates: 74, 76, 78, 80mm 4 x Pulling spindles with thrust bearings 20 x Press sleeves: 44 x 43; 46 x 36; 20 x riess sleeves. 44 x 45, 40 x 55; 48 x 38; 50 x 40; 52 x 42; 54 x 44; 56 x 46; 58 x 48; 60 x 50; 62 x 52; 64 x 54; 66 x 56; 68 x 58; 70 x 60; 72 x 62; 74 x 64; 76 x 66; 78 x 68; 80 x 70; 82 x 72mm Heat-treated forged carbon steel Sturdy Blow Mould Case









Kit 23 Piece 9029T TRADEQUIP

Hub screw length: 207mm

Hub screw drive: 32; 38mm

91 x 81.5; 102 x 92mm

Sleeve external: 76.5 x 65; 86 x 77;

Drift sizes: 50; 55; 59; 63; 66.5; 70; 71.5; 73; 73.5; 75, 77.5; 81.4; 83.3; 86; 88.4; 102mm





Universal Press & Pull Sleeve Kit 26 Piece

9024T TARADEQUIP

4 Beams 3 ½" Sleeves 20 Sleeves 11pieces (GOLD) 9 pieces (SILVER)



For removal and installation of bushes, bearings and seals, races, sprockets and pulleys on cars, trucks, off-road construction equipment and machinery



Hydraulic Gear Puller 23 Piece

9023T TRADEQUIP

Capacity: 10,000kg Bearing Separator: 20-105mm Twin/triple head, beam and legs to build: 100, 150 and 200mm Two and three leg hydraulic pullers with separator capacity: 75-105mm Size: 355L x 195W x 150Hmm

Pulls bearings, timing gears, steering wheels and pulleys on most cars and light trucks





Universal Press Support Block 30,000KG

9025T TRADEQUIP

Base block: 250 x 200 x 40mm Height adaptor block: 200x70x40mm

Made from Billet aluminium





For use with a hydraulic shop press for workpieces with a complicated shape to allow bearings to be pressed in or out accurately.













Code	7000T	7001T	7002T	7003T	7004T	7005T
Vice type	Fixed	Fixed	Fixed	Swivel	Swivel	Swivel
Jaw Width	125mm	150mm	200mm	125mm	150mm	200mm
Jaw Opening	130mm	150mm	170mm	140mm	170mm	220mm
Throat Depth	69mm	76mm	88mm	76mm	86mm	110mm
Anvil Size	85x90mm	100x105mm	105x105mm	106x106mm	127x127mm	147x147mm
Excl. GST	\$149	\$199	\$269	\$218	\$319	\$439
Incl. GST	\$163.90	\$218.90	\$295.90	\$239.80	\$350.90	\$482.90



Bench Offset Vice 150MM

7007T TADEQUIP

Jaw width: 150mm Jaw opening: 140mm Throat depth: 103mm Weight: 21kg



Excludes GST **\$388** Inc. GST \$426.80



Commercial Bench Vice Swivel with Anvil 150MM

BRV150 F= BORUM

Jaw width: 150mm Jaw opening: 150mm Throat depth: 105mm Anvil size: 90x105mm





Commercial Bench Vice Swivel with Anvil 200MM

BRV200 /= BORUM



DESIGNED FOR AUTOMOTIVE E INDUSTRIAL APPLICATIO

DON'T BE FOOLED BY CHEAPER IMITATIONS THAT ARE DESIGNED FOR DENTISTRY, MODEL BUILDING, OPTOMETRY & LIGHTER DUTIES

6 Litres TATRADEQUIP

Capacity: 6 Litres Ultrasonic power: 150W Ultrasonic frequency: 40KHz Heating power: 300W Heating temperature: 20-80 C

1036T

Timer range: 0-30 Minutes Tank material: 304 Grade 2mm thick Tank size: 300L x 155W x 150Hmm Size: 330L x 180W x 310Hmm

MADE FOR THE

13 Litres TATRADEQUIP

Capacity: 13 Litres Ultrasonic power: 300W Ultrasonic frequency: 40KHz Heating power: 400W Heating temperature: 20-80 C

Timer range: 0-30 Minutes Tank material: 304 Grade 2mm thick Tank size: 330L x 300W x 150Hmm Size: 360L x 330W x 310Hmm

1037T



* 30 Minute Timer

* Adjustable Temp. Control

* 304 Grade **Stainless** Steel Tank





27 Litres TATRADEQUIP

Capacity: 27 Litres Ultrasonic power: 500W Ultrasonic frequency: 40KHz Heating power: 500W

Heating temperature: 20-80 C

1038T

Timer range: 0-30 Minutes Tank material: 304 Grade 2mm thick Tank size: 500L x 300W x 200Hmm Size: 550L x 330W x 360Hmm

36 Litres TRADEQUIP

Capacity: 36 Litres Ultrasonic power: 600W (adjustable) Ultrasonic frequency: 28/40KHz Heating power: 800W Heating temperature: 20-80 C

Timer range: 0-30 Minutes Tank material: 304 Grade 2mm thick Tank size: 500L x 290W x 250Hmm Size: 570L x 360W x 450Hmm

1039T



LARGER SIZES AVAILABLE FOR SPECIAL ORDER. PLEASE ENQUIRE WITH YOUR PREFERRED DISTRIBUTOR.



Parts Cleaning Concentrate

ENVIRO FRIENDLY

BIODEGRADABLE

10 & 20 Litre 72 TRADEQUIP

Parts Washer 90 Litre

1003T TRADEQUIP

Pump power: 240V/50Hz/0.5A Pump output: 2.7-3.3 Litres per min. Tank: 758L x 527W x 275Hmm Minimum fluid capacity: 18 Litres Maximum fluid capacity: 45 Litres Size: 780L x 540W x 908Hmm



FEATURES

Sturdy metal construction and quality enamelled gloss finish.

Enclosed "High Volume" electric pump & fully screened pump housing.

Built-in replaceable pump inlet filter.

Chromed flexible metal fluid delivery pipe. Large removable parts cleaning shelf for inspection and drying.

Immersion soaking when parts cleaning shelf removed.

Non welded one-piece tank with Quick Close fire safe lid mechanism.

Suitable for use with aqueous water based cleaning fluids.

Replacement parts available



FORMULATED FOR USE IN ALL RADEQUIP PARTS CLEANERS

NON-TOXIC

Code	5083T	5082T
Bottle contents	10 Litres	20 Litres
Creates	50 Litres	100 Litres
Exi. GST	\$89	\$145
Incl. GST	\$97.90	\$159.50



Parts Washer 180 Litre

1004T TRADEQUIP

Pump power: 240V/50Hz/0.5A Pump output: 2.7-3.3 Litres per min. Tank:1135L x 545W x 320Hmm Min. fluid capacity: 33 Litres Max. fluid capacity: 90 Litres Size: 1150L x 560W x 1430Hmm



FEATURES

Sturdy metal construction and quality enamelled gloss finish. Enclosed "High Volume" electric pump & fully screened pump housing.

Built-in replaceable pump inlet filter. Chromed flexible metal fluid delivery pipe.

Large removable parts cleaning shelf for inspection and drying. Immersion soaking when parts cleaning shelf removed.

Non welded one-piece tank with Quick Close fire safe lid mechanism. Suitable for use with aqueous water based cleaning fluids

Replacement parts available



Parts Washer Brush & Hose



Long life 70mm synthetic bristles Polypropylene handle Stepped hose fitting suitable for connecting to 13mm and 16mm spouts Suits TradeQuip parts washers 1003T, 1004T & 1050

Stiff bristles are ideal for cleaning automotive and machined parts

Inc. GST \$30.80

WARNING: ONLY SUITABLE FOR USE VITH WATER BASED SOLUTIONS

Replacement Parts Washer Pump

1005 TRADEQUIP

Power: 230V 50Hz 26W 0.6Amp Cable length: 305mm Head max: 1.8m

Flowrate: 3.15 litres per minute Outlet thread: 1/2" NPT Female 100L x 85H x 65W mm

WARNING: ONLY SUITABLE FOR USE WITH WATER BASED SOLUTIONS



Inc. GST \$93.50

FEATURES

and 1050, sold separately)

Sturdy poly/plastic body. Stainless steel shaft. Suits parts washers with chromed flexible metal fluid delivery pipes Snap off inlet grill for easy cleaning.
Suitable for use with aqueous water based cleaning fluids.
Works with TradeQuip parts washers (Code/s 1003T, 1004T

Blasting Cabinet 220 Litre Capacity



Cabinet capacity: 220 Litre Working pressure: 60-110psi Maximum media capacity: 20kg
4 Ceramic nozzle tips: 4, 5, 6 & 7mm

With gun & low voltage internal fluorescent light Tempered glass view window: 250 x 525mm

External size: 1400H x 890L x 550Wmm Includes gun and light





Freestanding floor model. Complete with gun and low voltage internal fluorescent light. Tempered glass viewing window with

Cabinet fitted and ready to be used with a workshop vac as dust collection system. Spare parts available in Australia



Tempered

Side

opening

door

Blasting Cabinet 420 Litre Capacity

3036T TRADEQUIP

Cabinet capacity: 420 Litre Air regulator & gauge panel 4 Ceramic nozzles: 2x5mm, 2x6mm Maximum media capacity: 70kg Maximum air pressure: 125psi Required air supply: 15-25CFM 14 gauge steel legs & 16 gauge panels Sand blasting efficiency: 100cm²/min Optimum operating pressure 60-110psi External size: 1680H x 1180W x 940Dmm



Oversized hinged top door opening Includes 240V dust extraction system



Includes blasting gun and vinyl laster gloves

FFATURES

Perfect for surface preparation on any type where other forms of preparation are difficult.

lideal for removing paint, rust, scale and oxidation.

Large viewing window gives the

operator a wide viewing area.

Oversized hinged top door opening
& large inside work area allows easy
maneuverability.

Hinged door on hopper allows for easy

abrasive changes.
Fluorescent light kit and 90CFM dust collector help the operator to maintain a good visual.

Rear-mounted dust collector.

Replaceable protective window.Foot-pedal-controlled siphon blast gun.





Soda/Sand Blasting Hood

3053 TATRADEQUIP

Durable fabric & synthetic-leather construction Large 110mm x 55mm acrylic viewing plate Adjustable internal helmet for added comfort Reinforced side ventilation panels for increased airflow

FEATURES

Protect eyes and face from "rebounding" abrasive particles by wearing Abrasive Blasting Hood, Ideal for many abrasive blasting applications





BLASTING MEDIA ABRASIVE

TradeQuip "Made for the Trade" Blasting Media Abrasives are designed for use in conjunction with our TradeQuip Mobile Blasting Kits and Blasting Cabinets. Abrasive blasting has been used for many years to clean and remove rust, paint and corrosion. There are many types of abrasive media available, the most common being Garnet, Steel Grit and Glass Bead. These media have an aggressive cut and can rapidly remove paint and rust. However, they can also generate significant heat, potentially resulting in warped metal and etched surfaces, and they cannot be used on fibreglass. Also, chrome, plastic, rubber, trim, and other parts must be removed from a work surface or masked-off before blasting.

Alternatively, less-aggressive media, such as Walnut Shell, will do a great job at removing paint. Walnut Shell does not generate as much heat as other media, and can be used on sheet metal and fibreglass without damaging the base material. However, Walnut Shell as with any abrasive media, will require more clean-up as it leaves particles in the car body's seams and crevices that can be difficult to completely remove.

Soda blasting media has non abrasive properties which makes it a very universal blasting media which can be applied to lighter materials such as aluminium, plastic, fibreglass, wood etc. Soda Blasting does not damage glass, rubber, chrome items if they are left on a vehicle for blasting

GARNET 25KG MEDIUM 30/60 3020T TRADEQUIP

Garnet is a gemstone with excellent naturally abrasive properties. This hard abrasive is fast-cutting, low-dust producing and low-consuming, excellent for removing tough coatings, paint, rust and mill scale from steel. Garnet also permits precise feathering control. A good general outdoor surface preparation abrasive.



WALNUT SHELLS 20KG 6-100 MICRON 3022T TRADEQUIP

Walnut Nut shells and other organic materials, don't cause anchor patterns, making them useful for removing dirt, grease, oil, carbon, scale, burrs and paint without changing the underlying substrate. Walnut shells can be an excellent choice for softer surfaces such as wood — they won't cause etching. Walnut shells are one of less abrasive blasting media you can use and are completely biodegrad able, making them among the most environmentally-friendly



GARNET 25KG COARSE 20/40 3023T TRADEQUIP

Garnet is a gemstone with excellent naturally abrasive properties. This hard abrasive is fast-cutting, low-dust producing and low-consuming, excellent for removing tough coatings, paint, rust and mill scale from steel. Garnet also permits precise feathering control. A good general outdoor surface preparation abrasive



GLASS BEAD 25KG 106-300MICRON 3025T TARADEQUIP

Glass beads are used for general cleaning, peening and cosmetic finishing of sensitive metal surfaces; removing automotive paint; brightening grout and removing fungus and calcium deposits from tile; polishing cast iron, stainless steel, aluminium, propellers and turbine blades. Glass Beads are environmentally friendly and can be used in many blast applications to provide a finish with no profile. Use while working with metal, plastic or rubber materials to clean



SODA BI CARB 22KG TRADEQUIP 3028T (Product of America)

Clean tools, strip paint and more with Soda Bi-Carbonate. The medium-sized crystals provide blasting power to smooth and strip paint without damaging other surfaces. Works with aluminum, steel, stainless steel, fibreglass and more.





Mobile Blasting Kit 37 Litre Capacity

Tank capacity: 37 Litre Working pressure: 60-125psi Air delivery: 400-600 Ltr p/min. @ 125psi (dependent on nozzle size)

4 ceramic nozzle tips: 2.0 2.5 3.0 3.5mm Hose length: 2.4M 508H x 305Ø



MADE FOR THE

FEATURES

Heavy duty welded steel design. High volume extra large valve.

Designed for high flow with minimal air input. Blast gun fitted with safety trigger. Heavy-wall blast hose. Durable wheels Safety pressure-relief valve Safety mask, thread tape and refill funnel Onboard pressure regulator Easy to fill screw tank cap









Porta Power Kit 2011T 79 TRADEQUIP

Blow mould carry case: 530 x 500 x 110mm Weight: 24kg







INDUSTRIAL

OUALITY

Excludes GS

Set Includes: 4 x Hooks - 2 Large and 2 Small 2,000kg Mini Ram - Compressed 139mm > Stroke 76mm 4,000kg Mini Ram - Compressed 42mm > Stroke 16mm 10,000kg Mini Ram - Compressed 118mm > Stroke 60mm 4,000kg Porta Power Ram - Compressed 276mm > Stroke 132mm 10,000kg Porta Power Ram - Compressed 350mm > Stroke 150mm 2,000kg Pull Back Ram - Extended 537mm > Stroke 128mm 5,000kg Pull Back Ram - Extended 613mm > Stroke 130mm

Porta Power Kit BPP20T - BORUM

Safe working capacity: 20,000kg Extension tubes: 125, 255, 510, 700mm 3 each, 70mm connective tube & 60mm joint connector tube Base, Ram toe, Plunger toe Wedge toe, V-base, Wrench Retracted ram length: 285mm Ram stroke: 125mm Hydraulic hose length: 1470mm Inc. GST \$1582,90

Weight: 62kg **FEATURES**

Constructed of high-grade steel and built to exacting standards for quality and durability. Lead-free paint finish is oil, grease and dirtresistant for easy cleanup.
High quality hydraulic steel cylinder unit helps

to reduce wear and extend service life. Piston-ram is treated and polished. Hydraulics are powered with a high quality oil, which offers better corrosion resistance and high/low temperature flexibility Heavy walled extension tube





Air/Hydraulic Pump 2054T TRADEQUIP

Maximum output pressure: 10,000psi Usable hydraulic fluid capacity: 2.25 Litres Operating air pressure: 90-145 psi Air consumption: 7.5CFM @ 100 psi Oil delivery with No Load: 49.5 cu.in/min Oil delivery with Load: 7.6 cu.in/min Input (Air) port thread: 1/4" -18 NPT Output (Oil) port thread: 3/8" -18 NPT

FEATURES

Durable light-weight corrosion-free aluminium Built-in overload system prevents pump from being used beyond its safety capacity.

Ergonomic hand/foot activation lever. Air/oil filters minimise contaminants in hydraulic system Perfect for porta power rams & bead breakers Compact design fits in truck storage boxes. Air exhaust muffler for quiet operation.

2054H Hose to suit - \$189 ex gst \$207.90 inc gst



Porta Power Kit 2010T TOTRADEQUIP

Safe working capacity: 10,000kg 14 Piece Kit containing pump and hose fittings

Ram length retracted: 322mm Ram length extended: 452mm Extensions: 110.265.365.520mm Case: 905L x 385W x 175H mm Hydraulic hose length: 1500mm Hydraulic oil capacity: 650ml Adaptor diameter: 33mm Weight: 31kg



FEATURES

Spring loaded ram return system, allowing controlled retraction of the ram.

Pump may be used in horizontal & vertical position.

Constructed of high-grade steel and built to exacting standards for quality and durability.

Lead-free paint finish is oil, grease and dirt-resistant.

Pump has an automatic overload system.

Easily adapts to hoses, rams, pumps, spreaders, and other accessories using common 1/4" fittings



FEATURES

Durable steel construction

pump (sold seperately).

Clamps to wheel rim & breaks bead

simply with up to 5,000kg of force. Requires 10,000psi air/hydraulic

Combi Portable Bead Breaker 5,000KG

BTBB05 /= BORUM

Working load limit: 5,000kg Pressure connection: 3/8"-18NPTF Rated pressure: 10,000psi Maximum rim size: 26"

Suits 1,2 & 3 pce rims (up to 26") with pry bar / bead loosening pockets Ram stroke: 90mm

INDUSTRIA GUALIT



Giant Portable Bead Breaker 13,000KG

BTBB13 = BORUM

Working load limit: 13,000kg Pressure connection: 3/8"-18NPTF Rated pressure: 10,000psi

Suits 5 pce rims 635-1,295mm (25"-51") with pry bar / bead loosening pockets

Maximum rim size: 26' Ram stroke: 105mm

FEATURES

Economical solution for earthmover wheels 25" – 51" multi-piece rims with pry bar pockets.

Hydraulically clamps on wheel. Durable steel construction.

Hydraulic power breaks beads in seconds. Requires 10,000psi air/hydraulic pump

(sold seperately)







ALL BORUM DRILL PRESSES FEATURE

Flexible worklight. Engineering style work table. Oversize micro-switch activated safety quard.

Low-noise belt drive with cast iron balanced pullevs.

Safety ON-OFF switch fitted with a dust cover and positive action push buttons plus a large (Red) self locking "Emergency Stop" hinge cover. Precision spindle bearing for long life & high accuracy.

Table control via hand crank and gear rack with high load capacity. Long quill stroke, easy to adjust depth stop at the capstan handle.

Thick-walled, precision-ground column for extra rigidity.

Powerful long-life commercial drive motor provides high reliability. Ground set-up areas on table and base plate.

Solid rotating work table with diagonal clamping slots

The same reliable **'Heavy Duty Industrial Quality Drill Presses'** since we started manufacturing them in 1984... but with the benefit of some 21st Century features



1HP Pedestal Drill Press 16 Speed CH18FT Z BORUM

Motor: 240Volt 1HP

Number of speeds: 16 Spindle taper: MT2

Spindle speeds: 200-3160rpm Max. drilling capacity: 20mm Max. spindle stroke: 82mm

Max. distance spindle to table: 775mm Max. distance spindle to base: 1270mm

Chuck: 16mm Swing: 430mm

Table diameter: 350mm Diameter of column: 80mm Size of base: 460x270mm

Overall height: 1625mm







2HP Pedestal Drill Press 12 Speed CH30T /= BORUM

Motor: 240Volt 2HP Number of speeds: 12

Spindle taper: MT4 Spindle speeds: 210-2160rpm Max. drilling capacity: 32mm

Max. spindle stroke: 122mm Max. distance spindle to table: 720mm Max. distance spindle to base: 1230mm

Chuck: 16mm Swing: 535

Size of table: 473x410mm Diameter of column: 92mm Size of base: 572x495mm

Overall height: 1780mm





Visit our webpage for instructional & pre-start videos.









Motorcycle Lifter 360KG

MADE FOR THE

2102T TRADEQUIP

Safe working capacity: 360kg Height: 205 - 780mm Platform: 490W x 1345Lmm

Weight: 95kg



Motorcycle Scissor Lift 500KG

2104T TRADEQUIP

Safe working capacity: 500kg Height: 95 - 420mm Platform dimensions: 450x150mm Weight: 13.8kg

FEATURES

Designed to deliver the ideal lift for use with motorcycles, ATV's, tractors, personal watercraft, and snowmobiles.

Lifts back wheel off lift table for tyre/wheel Powder coated structural heavy duty steel

construction.

Rotate lead screw to adjust & raise the lift. Bolt down lugs to prevent unwanted movement.







Motorcycle Lifter 450KG 2101T TRADEQUIP

Safe working capacity: 450kg Height: 175 - 750mm Platform: 680W x 2200Lmm

Weight: 120kg







FEATURES

Ideal lift for use with motorcycles, ATV's, tractors, personal watercraft & snowmobiles. Locking bar for safety.

Powder coated structural heavy duty steel Extra Long Full width loading ramp.

Step-less rate of lowering irrespective of load. Oil trap plate for easy drainage.

2 foot pedals for raising & lowering - for easy

hands free operation.
Fitted with 2 position platform locking device

to prevent accidental lowering.

Quality wheels and swivel castors making it easier to position and move around. Lockdown bolts to prevent unwanted movement during use.

Does not include tie down straps





Motorcycle Lifter Air Actuated 680KG

2103T TRADEQUIP

Safe working capacity: 680kg Height: 185 - 825mm

Platform dimensions: 710 x 2000mm Required air pressure: 0.75-0.85Mpa

Weight: 169kg



FEATURES

Designed to deliver the ideal lift for use with motorcycles, ATV's, tractors, personal watercraft, and snowmobiles.
Locking bar for safety.
Extra long full width loading ramp.

Powdercoated structural heavy duty steel Stepless rate of lowering irrespective of the load

Oil trap plate for easy drainage.

Lockdown bolts. 2 foot pedals for raising & lowering - for easy hands free operation. Fitted with 2 position platform locking device





Workshop Trolley (Polymer) 6042T TRADEQUIP

TRADE

Safe working capacity: 226kg Tray: 900L x 600W x 65Hmm

Tray capacity: 113kg (each) Smooth rolling rubber castors: 125D x 25Wmm

Ground clearance: 140mm Weight: 22kg

cludes GST GST \$372.90

FEATURES

Two swivel and two fixed smooth rolling rubber castors.

No painting required. Cleans easily. Virtually maintenance free. MADE FOR THE **Workshop Trolley (Polymer)**

6045 TATRADEQUIP

Safe working capacity: 226kg 3 x 100mm deep shelves 125x30mm smooth rolling rubber swivel castors 75kg tool tray capacity 875L x 430W x 830Hmm

Excludes GST Inc. GST \$302.50

Capacity

FFATURES

Deep shelves for plenty of storage. Will not dent, rust or chip. Convenient push handle.
Two swivel and two fixed smooth rolling rubber castors.
No painting required. Cleans easily. Virtually maintenance free. **Workshop Trolley (Polymer)**

6043T TRADEQUIP Safe working capacity: 226kg

Two deep and wide shelves for plenty of storage. Convenient push handle. Virtually maintenance free.

Two swivel and two fixed smooth rolling rubber castors

Will not dent, rust or chip. No painting required. Cleans easily.

Tray capacity: 76kg (each) Trav: 900L x 600W x 65Hmm

Smooth rolling rubber castors: 125D x 25Wmm

Ground clearance: 140mm Weight: 33.5kg

Excludes GST

Inc. GST \$427.90

FFATURES

Workshop Trolley 3 Tool Trays

6004 TRADEQUIP

Safe working capacity: 150kg Powder coated .6mm steel 100mm composite castors 845L x 410W x 780Hmm

Excludes GST Inc. GST \$196.90

MADE FOR THE TRADE



FEATURES

This three shelf workshop tool trolley is durable enough for moving tools and car parts. Deep shelves give you plenty of storage for your tools and parts.

150kg Capacity

Workshop Trolley 2 Tool MADE FOR THE

Trays & 1 Drawer



Safe working capacity: 100kg One lockable drawer 100mm composite rubber castors Two 100mm deep shelves 770L x 370W x 830Hmm



FFATURES

Heavy gauge steel construction 35mm ball bearing slide drawer. Side handle for comfort and control. Tough enamel finish.



Workshop Trolley (Polymer)

Three deep and wide shelves for plenty of storage. Convenient push handle. Virtually maintenance free.
Two swivel and two fixed smooth rolling rubber castors.
Will not dent, rust or chip. No painting required. Cleans easily.



Safe working capacity: 226kg 8 Parts bins 241x152x127mm 24 Parts bins 165x101x76mm 125x30mm rubber swivel castors 85kg tool tray capacity 1000L x 435W x 850Hmm

Deep shelves give you plenty of storage for your tools and parts. Industrial grade castors.

Will not dent, rust or chip.

Convenient push handles.

No painting required. Cleans easily.



Inc. GST \$416.90





Capacity: 65 Litres Working height: 1080-1600mm Discharge pressure: 12psi Telescopic adjustment Air inlet: 1/4" BSP

> TELESCOPIC COLLECT STORE/CARRY DISCHARGE

MADE FOR THE

FEATURES

Collect, transfer, evacuate used engine oils, transmission fluids, power steering fluids etc. Top quality heavy-gauge

steel collection tank with adjustable telescopic drain pan. Offset drain bowl and Tank

oil level indicator. Air pressure relief valve prevents.

Sturdy rubber front wheels and ball bearing-mounted rear castors provide stability and easy maneuverability. Lead-free paint is oil, grease and dirt-resistant. Oil, heat, ozone and abrasion resistant hose



Truck Fluid Drain Pan 60 Litre

1146T TRADEQUIP

Capacity: 60 Litres Enamel steel construction Oil and coolant resistant Size: 1174 x 641 x 673mm Front swivel castors

MADE FOR THE

FEATURES

Enamelled steel construction Oil and coolant resistant. Removable metal screen Two front swivel castors. Two rear fixed wheels Brass drain valve. Transfer pump coupling.









1147T TATRADEQUIP Lightweight high-impact polypropylene.

Oil and coolant resistant Manoeuvrable 4" castors Tank size: 1300x730x200mm



FEATURES

Lightweight high-impact polypropylene. Suitable for engine oil, coolant and transmission fluid.

Built-in rotary hand discharge pump. Removable metal filter screen Smooth rolling rubber castor wheels





Built-in rotary hand discharge pump



Inc. GST \$636.90

Truck Fluid Drain Pan 95 Litre

1145T TRADEQUIP

Capacity: 95 Litres Minimum tray clearance: 196mm Reservoir dimensions:

910L x 725W x 165Hmm Size: 1120L x 780W x 195Hmm

FEATURES

Enamelled steel construction Oil and coolant resistant. Removable metal screen. Four swivel wheels, two which are braked. Handle can be mounted to front or side Drain valve & Grab handle

Removable metal filter screen

Handle can also be mounted



Excludes GST Inc. GST \$449.90



1520mm

90kg Capacity

Steel Workbench

1014T TO TRADEQUIP

Safe working capacity: 90kg Work surface: 1510x700mm Raised edge height: 50mm 1520L x 710W x 830Hmm Weight: 48kg

FEATURES

Sturdy steel construction. High gloss enamel paint finish Raised protective edge to work surface Adjustable feet for levelling on uneven floors. Quick and easy to assemble.

Easily wipe dirt and grime from surface with a soft cloth.

MADE FOR THE

50mm hịgh raised

Heavy duty steel construction High gloss enamel paint finish

Includes bottom shelf & 3 locking drawers Each drawer holds up to 50kg 2000L x 860H x 640Wmm

1012T TATRADEQUIP

Safe working capacity: 300kg

Manufactured from high quality, heavy-duty steel and features a large surface for more work space and an extended lip around the surface of the table.

The tough high gloss enamel paint finish is designed to provide years of protection against normal wear and tear.

2000mm



Inc. GST \$812.90

300kg Capacity

MADE FOR THE

3 Drawer Steel Workbench

Excludes GST GST \$907.50

Mobile Workbench MADE FOR THE

Excludes GS1

6047 TRADEQUIP

Safe working capacity: 250kg Bench top capacity: 150kg Bench top: 1200L x 640Wmm 1200L x 640W x 875H mm Shelf: 1110L x 460Wmm Shelf capacity: 100kg

Weight: 56.5kg **FEATURES**

Heavy duty rolled edge steel construction. Convenient removable drain bowl. 13mm benchtop rim to contain leaking fluids when working on engines and transmissions. Quality castors (2 swivel

with brake). Lockable steel drawer with ball bearing slides

Mobile Bench

1073T TRADEQUIP

Safe working capacity: 300kg Work surface: 1100 x 700mm 1100L x 700W x 830H mm Weight: 60kg

FEATURES

Sturdy steel construction. High gloss enamel finish. Heavy-duty handle Quality castors - two fixed & two locking swivel.

1100mm



MADE FOR THE

TRADE



22 Bin Parts Storage Rack

6053 TARADEQUIP

Working load capacity: 100kg 15 parts bins: 345x105x75mm (3kg load capacity) 4 parts bins: 345x140x150mm (5kg load capacity) 3 parts bins: 345 x 205 x 150mm (8kg load capacity)

Swivel castor diameter: 100mm 8801 x 410W x 950H mm

Quality swivel castors (2x lockable).

Convenient access to removable bins



36 Bin Parts Storage Rack

6054 TRADEQUIP Working load capacity: 200kg

15 parts bins: 345x105x75mm (3kg load lapacity) 12 parts bins: 345x140x150mm

(5kg load lapacity)

9 parts bins: 345 x 205 x 150mm (9kg load lapacity)

Swivel castor diameter: 100mm 880L x 410W x 1705Hmm

ADE FOR THE

Inc. GST \$757.90

FEATURES

Sturdy nine-tier steel powder coated rack Zinc plated wire shelving with bin locating guides Quick & easy clip together adjustable shelves. Stackable bins made of moulded polypropylene ldeal for garage, workshop, office, shed. Powder coat frame resists corrosion. Quality swivel castors (2x lockable). Convenient access to removable bins



ASSEMBLE



Mobile Workshop Table with Drawer

Lockable composite

6056T TRADEQUIP 340x300x45mm drawer Adjustable from 860-1200mm high Includes drawer and top tray liner 80kg Distributed load capacity 730x500x25mm top tray

FEATURES

Height adjustable for most Ball Bearing wheels for easy moving.
Multi-functional top table with 3 compartments and

Inc. GST \$401.50

6 screwdriver holes. Top EVA mat for skid resistance. Extra drawer for more

Truck Mobile Workshop Table BMWST BORUM

MADE FOR THE

Safe working capacity: 34kg Adjustable working height: 960-1500mm Distance between front casters: 955mm

Caster wheel diameter: 75mm Table top: 797L x 695W Main tray: 556L x 695W Depth at full width: 485mm



INDUSTRIAL QUALITY

Height adjustable to most commercial vehicles. Smooth rolling casters Extra wide legs to suit commercial vehicles.
Multi-functional top table with 2 compartments and 8 screwdriver

Top EVA mat for skid resistance. Protective bumper for top tray. Strong tubular steel construction Sturdy main support post.



Workshop Trolley 2 Drawers & Lockable Sliding Top

6019T TATRADEQUIP

Safe working capacity: 100kg Two lockable drawers & top 100mm composite rubber castors Two 75mm deep shelves

> MADE FOR THE TRADE

700L x 370W x 760Hmm

FEATURES

Heavy gauge steel construction with lockable sliding top. Quality 35mm ball bearing sliding drawers, which are locked when top is closed. Side handle for comfort/control when moving.

Tough enamel finish.
Non slip rubber tool tray liners

100kg Capacity

Inc. GST \$423.50

Excludes GST

Workshop Trolley Single Drawer 6020T TRADEQUIP

Safe working capacity: 155kg Lockable drawer: 635L x 320W x 80Hmm Top storage tray: 695L x 405W x 65Hmm

Lower storage tray: 750L x 395W x 68Hmm Rubber castors: 100Dmm 775L x 415D x 890Hmm



Inc. GST \$295.90

Heavy gauge steel construction with lockable drawer on smooth runners. Two top mounted handles for added control when manoeuvring. Tough enamel finish. Non slip EVA foam tool tray liner. Two heavy-duty locking swivel casters for control and maneuverability. Large top & bottom shelf giving

TRADEQUIP 155kg Capacity

Excludes GST

Inc. GST \$515.90

Workshop Trolley 4 Drawers with Lockable Top

6052 TATRADEQUIP

Safe working capacity: 260kg

4 lockable drawers on 35mm ball bearing slides Two 75mm deep shelves for plenty of storage (one lockable)

Top 2 drawers (each): 310W x 370D x 50Hmm Middle drawer: 680W x 370D x 70Hmm

Large drawer: 660W x 370D x 100Hmm Two swivel and two fixed 100mm smooth rolling

composite rubber castors. 850L x 445D x 972Hmm



Heavy gauge steel construction with lockable sliding top on smooth ball bearing runners. Quality ball bearing slide drawers, that lock when top is closed. Side handle for comfort and control when manoeuvring.
Tough high gloss enamel finish. Non slip rubber tool tray liners. Heavy-duty ergonomic grip handle. Two heavy-duty locking castors for control and stability





EDGLE PRO

ABOUT EAGLE PRO HYDRAULICS

With nearly 3 decades experience of manufacturing hydraulic tools for industrial applications, Eagle Pro Hydraulics has become the trusted partners for applications spanning from offshore plant maintenance to mining, infrastructure, commercial and industrial. Eagle Pro Hydraulics are manufactured to ISO 9001:2018 through international quality assurance programs which involve consistent observation of administration, management, manufacturing and production control. Eagle Pro hydraulic cylinders meet or exceed ANSI B30.1. This results in reliable and dependable high-quality products you can count on every time.

ES SERIES

Single Acting General Purpose

Eagle Pro ES series redefines durability for the harshest of industrial environments with its high strength alloy steel construction. Hardened and chromed piston ensures superior product life by reducing wear and corrosion.

Eagle Pro ES series is not only durable, it gets the job done! Heavy-duty, straight pull return springs provide fast retraction. For greater flexibility and easy mounting, the ES series comes with collar, multiple piston threads, and base mounting holes. Hardened and E-coated snap-in type saddle prevents piston jamming and mushrooming, practically eliminating downtime. The female coupler comes with a dust cover – preventing dirt and debris from entering the hydraulic system.

The Eagle Pro ES series also complies with ASME B30.1 standard.



EDH SERIES

Double Acting Hydraulic

The Eagle Pro EDH series incorporates a hollow piston design that allows both pushing and pulling forces. The construction of high strength alloy steel maximizes durability. The EDH series' double acting operation ensures fast and controlled piston reaction time.

Accidental over-pressurization is prevented with a built-in safety valve. The collar, piston threads, and base mounting holes enable easy fixturing.



ED SERIES

Double Acting General Purpose

The Eagle Pro ED series produces fast and controlled piston contraction thanks to the double acting operation.

A built-in safety valve prevents accidental-over pressurization. Most models include collar, piston threads, and base mounting holes to make fixturing a simple task.

Piston jamming and mushrooming is prevented by the cylinder's hardened, and E-coated snap-in saddle. The ED series enhances durability with a hardened and chromed piston that reduces wear and corrosion. ED series cylinders are easy to move around the job site with the addition of carrying handles (and eyebolts on larger models) that ease positioning and carrying. A durable, anti-corrosive finish is added using an environmentally friendly coating process.





EDX SERIES

Double Acting High Tonnage

Eagle Pro EDX series maximizes durability with the use of a high strength alloy steel. The built-in safety valve prevents accidental over-pressurization. The EDX is easy to carry and position with the included eyebolts. Optional tilt saddles are also available. The hardened and chromed piston minimizes wear and corrosion damage. The incorporation of base mounting holes enables easy fixturing. An environmentally friendly coating process provides a highly durable finish.



EDX-1002T

EL SERIES

Single Acting With Locking Collars

The Eagle Pro EL series includes an alloy steel lock nut for mechanical load holding. The EL series is constructed of a high strength alloy steel to maximize durability. The hardened chrome piston reduces damage caused from wear and corrosion. The over flow port functions as a stroke limiter.

The EL series includes hardened grooved replaceable saddles. Composite bearings prevent metal-to-metal contact. Quick reaction times are obtained through with heavy-duty straight pull return springs. An environmentally friendly coating process produces a finish that further increases durability.



ESL SERIES

Low Profile And Pancake Style

Featuring a low-profile, or flat design, the Eagle Pro ESL series cylinder is an optimal choice for confined spaces. The hardened and chromed piston is constructed of high strength alloy steel that increases durability by reducing wear and corrosion.

The grooved piston end does not require a saddle and the inclusion of mounting holes permits easy fixturing.

Retraction time is quick thanks to the heavy duty, straight pull return springs. An environmentally friendly coating process is used to provide the durable anti-corrosion finish.



ESH SERIES

Single Acting Hollow Piston

The Eagle Pro ESH Series allows for both pushing and pulling by incorporating a hollow piston design. The heavy-duty return spring provides notoriously quick reaction times. Easy fixturing with the inclusion of collar threads.



EPA SERIES

Dual Speed Hand Pumps

The Eagle Pro EPA series hydraulic hand pumps are some of the most durable, powerful and reliable hand pumps in the industry today. The EPA series feature valve blocks that are machined from a single piece of high strength aircraft grade aluminum and high capacity reservoirs made from alloy steel* that maximizes durability. The EPA series hand pumps are compact and easy to carry around the job site. To get the job done faster, these powerful dual speed pumps offer some of the best flow rates in the industry. All of the EPA series hydraulic hand pumps feature an internal safety valve to prevent system damage.





TEAGLE PROPERTIES





ı										
ı			Cylinder Capacity @ 10,000PSI	Ctvolco	Cylinder Effective	Oil Canacity	Collapsed Height	Extended Height	Price	Price
	Model	Description	(700 BAR)	Stroke	Area	Oil Capacity	A	В	ex GST	inc GST
			Metric Kg	MM	CM ²	CM ³	MM	MM		
	ES-50	SINGLE ACTING RAM	5,000	16	7.1	11.4	42	58	\$399.00	\$438.90
	ES-51	SINGLE ACTING RAM	5,000	25	7.1	17.8	110	135	\$489.00	\$537.90
ı	ES-55	SINGLE ACTING RAM	5,000	127	7.1	90.2	215	342	\$619.00	\$680.90
I	ESL-50	SINGLE ACTING RAM PANCAKE STYLE	5,000	6	7.1	4	33	39	\$389.00	\$427.90
	ES-1010	SINGLE ACTING RAM	10,000	257	14.5	372.65	349	606	\$799.00	\$878.90
Ī	ES-102	SINGLE ACTING RAM	10,000	54	14.5	78.3	121	175	\$489.00	\$537.90
I	ES-106	SINGLE ACTING RAM	10,000	156	14.5	226.2	247	403	\$799.00	\$878.90
	ESL-100	SINGLE ACTING RAM PANCAKE STYLE	10,000	10	14.5	15	42	53	\$569.00	\$625.90
Ī	ESL-101	SINGLE ACTING RAM PANCAKE STYLE	10,000	38	14.4	55	88	126	\$599.00	\$658.90
	ESH-121	SINGLE ACTING RAM HOLLOW PISTON	13,000	42	18.4	77.3	120	162	\$969.00	\$1065.90
Ī	ES-1510	SINGLE ACTING RAM	15,000	254	21.2	538.48	373	627	\$1099.00	\$1208.90
Ī	ES-1514	SINGLE ACTING RAM	15,000	356	21.2	754.72	474	830	\$1199.00	\$1318.90
ı	ES-152	SINGLE ACTING RAM	15,000	51	21.2	108.12	149	200	\$759.00	\$834.90
ď	ES-154	SINGLE ACTING RAM	15,000	101	21.2	214.12	200	301	\$929.00	\$1021.90
ı	ESH-206	SINGLE ACTING RAM HOLLOW PISTON	20,000	49	32.8	161	162	211	\$1749.00	\$1923.90
I	ESL-200	SINGLE ACTING RAM PANCAKE STYLE	20,000	11	28.3	31	51	62	\$699.00	\$768.90
ı	ESL-201	SINGLE ACTING RAM PANCAKE STYLE	20,000	45	28.3	127	98	143	\$769.00	\$845.90
	ES-251	SINGLE ACTING RAM	25,000	26	33.2	86.32	139	165	\$999.00	\$1098.90
	ES-252	SINGLE ACTING RAM	25,000	50	33.2	166	165	215	\$1079.00	\$1186.90
	ES-254	SINGLE ACTING RAM	25,000	102	33.2	338.64	215	317	\$1179.00	\$1296.90
\	ES-256	SINGLE ACTING RAM	25,000	158	33.2	524.56	273	431	\$1349.00	\$1483.90
\	ESH-302	SINGLE ACTING RAM HOLLOW PISTON	30,000	64	48	307	179	242	\$1888.00	\$2076.80
	ESH-306	SINGLE ACTING RAM HOLLOW PISTON	30,000	156	48	744	330	485	\$1999.00	\$2198.90
	ESL-300	SINGLE ACTING RAM PANCAKE STYLE	30,000	13	41.8	54	58.5	71	\$1055.00	\$1160.50
1	ESL-302	SINGLE ACTING RAM PANCAKE STYLE	30,000	62	41.8	259	117	179	\$979.00	\$1076.90
	EL-506	SINGLE ACTING RAM LOCKING COLLAR	50,000	150	70.8	1062	264	414	\$1929.00	\$2121.90
	ES-502	SINGLE ACTING RAM	50,000	51	70.9	361.59	176	227	\$1229.00	\$1351.90
\	ES-506	SINGLE ACTING RAM	50,000	159	70.9	1127.31	282	441	\$1699.00	\$1868.90
	ESL-500	SINGLE ACTING RAM PANCAKE STYLE	50,000	16	63.6	102	67	83	\$979.00	\$1076.90
	ESL-502	SINGLE ACTING RAM PANCAKE STYLE	50,000	60	63.6	382	122	182	\$1199.00	\$1318.90
	ESH-603	SINGLE ACTING RAM HOLLOW PISTON	60,000	76	87.4	664	247	322	\$3199.00	\$3518.90
	EL-1002	SINGLE ACTING RAM LOCKING COLLAR	100,000	50	132.7	663.5	187	237	\$2399.00	\$2638.90



		Cylinder Capacity		Max. Cylind	der Capacity	Cylinder Effe	ctive Area	Oil Ca	pacity		
Model	Description	@ 10,000PSI (700 BAR)	Stroke	Advance	Retract	Advance	Retract	Advance	Retract	Price ex GST	Price inc GST
		Metric Ka	MM	METRIC TON	METRIC TON	CM ²	CM ²	CM ³	CM ³	EX 031	IIIC UST
										44=00.00	440=0.00
EDX-506	DOUBLE ACTING RAM	50,000	150	53	26	75.4	36.9	1,131	1,131	\$1799.00	\$1978.90
EDX-1006T	DOUBLE ACTING RAM	100,000	150	93	43	132.7	61.9	1,991	928	\$2549.00	\$2803.90
EDH-307	DOUBLE ACTING RAM HOLLOW PISTON	30,000	178	33	22	47.7	32.4	849	577	\$2249.00	\$2473.90
EDH-603	DOUBLE ACTING RAM HOLLOW PISTON	60,000	89	60	39	87.4	56.2	778	481	\$2549.00	\$2803.90
EDH-606	DOUBLE ACTING RAM HOLLOW PISTON	60,000	166	60	39	87.4	56.2	1451	891	\$3199.00	\$3518.90
ED-1012	DOUBLE ACTING RAM	10,000	305	10	3	14.5	4.9	443	149.5	\$1799.00	\$1978.90

				Usable Oil	Pressure	Rating	Oil Displacem	ent Per Stroke	Handle		
Model	Description	Cylinder Type	Speed	Volume	1st Stage	2nd stage	1st Stage	2nd Stage	Force	Price ex GST	Price inc GST
				CM ³	BAR	BAR	CM ³	CM ³		EX 031	IIIC UST
EPA-10921A	HAND PUMP, S/A, TWO SPEED, 55 IN3	SINGLE ACTING	TWO	750	25	700	33	3.3	49	\$699.00	\$768.90
EPA-12321A	HAND PUMP, S/A, TWO SPEED, 140 IN3	SINGLE ACTING	TWO	2300	25	700	33	3.3	49	\$1019.00	\$1120.90
EPA-12322A	HAND PUMP, D/A, TWO SPEED, 140 IN3	DOUBLE ACTING	TWO	2300	25	700	33	3.3	49	\$1039.00	\$1142.90

Model	Description	Internal Diameter	Length	Hose	Working Pressure	Burst Pressure	Hose End (Configuration	Price	Price	
Model	Description	MM	MM	Material	PSI	PSI	Pump End	Cylinder End	ex GST inc	inc GST	
EH-8206F	1/4" IDX6' RBR HYDHOSE 3/8" NPT EAB-201B	6	1800	-	10,000	20,000	3/8" NPT	3/8" NPT	\$199.00	\$218.90	

	Model	Description	Max. Pressure	Type	Thread	Female Coupler	Male Coupler	Price	Price
ı	Model	Description	PSI	туре		Ferriale Coupler	Male Couplei	ex GST	inc GST
	EAB-201	3/8" MALE/FEMALE HIGH FLOW QUICK	10,000	HIGH FLOW	3/8" - 18NPT	EAB-201A	EAB-201B	\$85.00	\$93.50

Model		Description	Pressure Range		Thread Gauge Diame		Price	Price
	Description	PSI	MPa		IN	ex GST	inc GST	
	EG-2510	2.5 IN. 15,000 PSI PRESSURE GAUGE	0 - 15,000	0 - 100	1/4" - NPT	2.5	\$239.00	\$262.90

Model	Description	Male Coupler Thread	Female Coupler Thread	Gauge Port Thread	Price	Price	
	Model	Description	IN/D	IN/E	IN/C	ex GST	inc GST
	EGA-005	GAUGE ADAPTOR	3/8" - NPT	3/8" - NPT	1/4" - NPT	\$89.00	\$97.90

	Model	Description	Cylinder Capacity @ 10,000 PSI (700 BAR)	Oil Capacity	Tip Clearance	Maximum Spread Distance	Cylinder Effective Area	Weight	Veight Price ex GST	
			US TON	CM ³	MM/A	MM/B	CM ²	KGS	ex doi	inc GST
	EFS-14	14 TON HYDRAULIC SPREADER	14	78.33	6.09	81.02	14.51	7.17	\$2389.00	\$2627.90



Portable Evaporative Cooler 750W

1029T TRADEQUIP

MADE FOR THE 240V/50Hz/750W 3 speed motor Max. air flow: 23,000 m3 per hour Water consumption: 20-35 litres per hour Effective cooling area: 200-260sqm Cooling area: 200-260m2

Water tank capacity: 200 Litres 1800H x 1600W x 780Dmm

Weight: 128kg

UPGRADED 5 BLADE DESIGN INCREASING AIR VELOCITY



Nylon Castors for easy portability

TRADEQUIP EVAPORATIVE COOLERS FEATURES & BENEFITS

Remote Control Timer Panel

Moulded polyethylene housing will not crack and is rust & leak proof. Environmentally-friendly alternative to traditional reverse cycle A/C. Cools without chemicals or refrigerants.

Long-term dependability. Near maintenance free operation.

Cools where traditional cooling methods are impractical or cost-prohibitive. Remote control speed adjustment. Direct drive. LCD 24 hour timer panel.

Easy to read water level sight tube gauge. Dual pour in refill water inlet and/or 3/4" hose fitting for automatic tap refill. Adjustable water flow & drain valve. Nylon castors for easy portability



Portable Evaporative Cooler 550W

1027T TRADEQUIP

240V/50Hz/550W 3 speed motor Max. air flow: 18,000 m3 per hour Effective cooling area: 100-150sqm

Water consumption: 12-18 litres per hour Water tank capacity: 100 Litres

1510H x 1120W x 680Dmm Weight: 58kg





Remote Control Timer Panel



Maintenance



Cooler Cover 1035T-CO TRADEQUIP

Water-resistant fabric Lightweight and breathable UV treated and Easy to use To protect 1027T, 1028T and 1035T TradeQuip Portable Evaporative Coolers when not in use.





Portable Evaporative Cooler 750W

1035T TRADEQUIP

240V/50Hz/750W 3 speed motor Max. air flow: 23,000 m3 per hour Effective cooling area: 150-200sgm Water consumption: 12-18 litres per hour

Water tank capacity: 130 Litres 1730H x 1120W x 680Dmm Weight: 63kg

Synchronous



Remote Control Timer Panel



Excludes GST Inc. GST \$1923.90



MADE FOR THE

Apply

Portable Industrial Spot Cooling Air Conditioners TATRADEQUIP

Code	1031T	1032T	1033T	
Power Unit	240V 50Hz	240V 50Hz	240V 50Hz	
Rated Power	950W	2000W	3000W	
Mains Plug	10 Amp	15 Amp	15 Amp	
Cooling Capacity	2.7KW/9200Btu	4.5KW/15300Btu	6.5KW/22200Btu	
Max. Air Flow	400m3 p/hr	800m3 p/hr	1200m3 p/hr	
Noise Level	55dB(A)	60dB(A)	65dB(A)	
Operating Temp.	18º - 45º C	18º - 45º C	18° - 45° C	
Suction Pressure	2.5Mpa (Max.)	2.5Mpa (Max.)	2.5Mpa (Max.)	
Discharge Pressure	4.5Mpa (Max.)	4.5Mpa (Max.)	4.5Mpa (Max.)	
Dimensions	855Hx430Wx405D	1035Hx520Wx480D	1245Hx640Wx560D	
Excl. GST	\$1599	\$3199	\$4399	
Incl. GST	\$1758.90	\$3518.90	\$4838.90	



TRADEQUIP INDUSTRIAL AIR CONDITIONERS FEATURES & BENEFITS

Compact yet powerful. Wide operating range of 18°- 45°C.

Single duct system for easy installation. Capillary tube construction for simplicity.

5 Litre self-contained condensation tank for easy removal and emptying.

Heavy duty compressor with automatic restart and short cycle protection.

Motors and compressors have overload protection.

Durable and long lasting steel construction.

Heavy duty locking castors and handles for easy manoeuvrability.

Easy to use plug in and place the hot air duct out of window/door or into false ceiling.

TradeQuip "Made for the Trade" Portable Air Conditioners offer a quick spot cooling solution with strong air flow and easy installation.





Motor: 240V/50Hz 10A 230W Air delivery: 720cubic metres per hour

Noise level: 76dB(A) Fuel consumption: 2.4kg/hr Tank capacity: 38 Litres

Dimensions: 880 x 456 x 590mm

Weight: 21kg



RUNS UP TO 9 HOURS ON A SINGLE FILL

FEATURES

Burns diesel or kerosene. Built in oil burner Electronic flame control system Safety overheat thermostat and pressure switch. Stainless steel heat exchanger.

Double skinned combustion chamber for thermoacoustic insulation and safe low surface temperature. Preheated oil filter. Twist lock fuel cap with cable. Pre-purge and post-ventilation cycles



Excludes GST Inc. GST \$823.90



Workshop Heater 50kW

1097T TRADEQUIP

Power output: 50kW - 170,600 Btu/h Motor: 240V/50Hz 10A 340W

Air delivery: 1100 cubic metres per hour

Noise level: 77dB(A)

Fuel consumption: 4kg per hour

Tank capacity: 56 Litres

Dimensions: 1090 x 490 x 585mm

Weight: 27kg

RUNS UP TO 9 HOURS ON A SINGLE FILL

FEATURES

Burns diesel or kerosene. Built in oil burner. Electronic flame control system Safety overheat thermostat and pressure switch. Stainless steel heat exchanger Double skinned combustion chamber for thermo-

acoustic insulation and safe low surface temperature. Preheated oil filter. Twist lock fuel cap with cable. Pre-purge and post-ventilation cycles

Limited Stock

ADE FOR THE

SEASONAL LINE

Limited

Stock

SEASONAL LINE

Excludes GS1

Inc. GST \$933.90