



Product Code: 1907T

## TELESCOPIC EVACUATING

## OIL DRAINER EXTRACTOR

90LITRE SAFE WORKING CAPACITY

TradeQuip waste oil evacuators take oil draining convenience and efficiency to the next level, by sucking hot oil from engines and transmissions via the dipstick tube or the traditional (under hoist) large oil drain pan. This vacuum-charged unit is completely portable and easy to use. Included are 3 different suction probes equipped with quick-disconnect couplers for fluid extraction. The transparent recovery chamber reservoir acts as a vacuum receiver operated by simple venturi and flow control valves.





## FEATURES

- Steel fabricated 90Litre discharge tank
- Height adjustable steel drain pan with grid filter
- Gravity feed reservoir with air discharge hose
- Includes quick release oil dipstick probes
- Fitted with reservoir oil level indicator tube
- Heavy-duty wheels & castors for easy mobility



## **SPECIFICATIONS**

- Discharge tank capacity: 90 Litres
- Transparent recovery chamber capacity: 10 Litres
- Vacuum Working Pressure: 0.04 0.06MPa
- Degree of Vacuum: 0.05 0.07MPa
- Suction Rate: 1.5-2 Litres per min using 6mm probe at oil temp 80°C
- Max Discharge Pressure: 12psi
- Discharge Hose Length: 1940mm
- Discharge Rate: 3-3.5 Litres per min
- Dimensions: 500 x 500 x 1850mm
- Weight: 39kg

